

FTN 2-S-A-A-DS6, C 2



dishwashing machine (belt-type)
Hobart
FTN 2-S-A-A-DS6, C25

Dimensions : 7100 x 865 x 1920 mm
connection : 42 kW - 400/3/50

belt conveyor dishwasher

capacity up to : 3244 plates/hr.

- loading zone no. 2 with power
pre wash zone S
length : 2000 mm
- main wash zone AA with treble
rinse zone
length : 2300 mm
- dry zone DS and exit zone 6
length : 2800 mm
- conveyor width : 612 mm
- compartment height : 400 mm
- working height : 920 mm
- height of legs : 150 mm
- width of machine with door
of connecting box
(removable) : 980 mm
- working direction : on choice right/left
or left/right

loading and pre wash zone 2S :

module length : 2000 mm
loading height : 920 mm
free loading zone : 740 mm
capacity pre wash tank: 125 ltrs.
pre wash pump : 2,2 kW
pump capacity : 660 l/min
temperature : 45-50°C

wash zone AA with 2 wash tanks, treble
rinse system consisting of
pre wash, circulated wash and
freshwater rinse :

module length : 2300 mm
hood : 2300 mm
tank volume/tank : 125 ltrs.
tank heating/tank : 9 kW
pump capacity : 2,2 kW/tank
water circulation : 900 ltrs./min.
obere Wascharme : 6
bottom washarms : 5

treble washing system

duo-plus rinse pump : 0,18 kW
consumption : 360 l/hr.
regeneration : 160 l/hr.
rinse temperature : 82-87°C
circulation temperature : 60-70°C
top rinse nozzles : 7
botto, rinse nozzles : 7
circulation nozzles top : 7
circulation nozzles bottom : 7
circulation pump : 0,55 kW#
capacity circulation-
pump : 1200 l/hr.
tank volume : 20 ltrs.

rinse booster for
treble rinse system:

electric heating

booster capacity
(coldwater-inlet) : 18 kW
booster volume : 20 l

dry zone DS and exit zone Nr. 8 :

module lenth dry zone : 1400 mm
free exit zone : 1400 mm
unloading height : 920 mm
heating capacity : 6 kW
ventilator : 1,95 kW
temperature : 50-55°C
air volume : 2200 m3/hr.

dishwashing machine (belt-type)

Isselbaecher
kitchen equipment GmbH

relative air humidity : 20 %

energy recovery system :

heat exchange : air into water
cooling surface : 25 m²
exhaust ventilator : 0,10 kW
exhaust volume : 1000 m³/hr.
temperature : 35°C
relative air humidity : 90 - 98 %
heat recovery system : approx 13 kW

included in price :

- cladding ar rear side
- door insulation
- Autotimer
- conveyor start-stop switch (start of conveyor)
- check valve 3/4" for cold and warmwater-intake
- 2 split points between pre- and 1. washing zone and between rinse and dry zone
- main switch

FTN 2ES-A-DS6-C25



dishwashing machine (belt-type)
Hobart
FTN 2ES-A-DS6-C25

Dimensions : 7100 x 865 x 1920 mm
Anschlusswert: 42 kW - 400/3/50

belt conveyor dishwasher

capacity up to : 3244 plates/hr.

- loading zone no. 2 with power pre wash zone S
length : 2000 mm
- main washine zone AA with treble rinse zone
length : 2300 mm
- dry zone DS and exit zone 6
length : 2800 mm
- conveyor width : 612 mm
- compartment high : 400 mm
- working height : 920 mm
- height of legs : 150 mm
- with of machine with door of connecting box (removable) : 980 mm
- working direction : on choice right/left or left/right

loading and pre wash zone 2S :

module length : 2000 mm
loading height : 920 mm
free loading zone : 740 mm
capacity pre wash tank: 125 ltrs.
pre wash pump : 2,2 kW
pump capacity : 660 l/min
temperature : 45-50°C

wash zone AA with 2 wash tanks, treble rinse system consisting of pre wash, circulated wash and freshwater rinse :

module length : 2300 mm
hood : 2300 mm
tankvolume/tank : 125 ltrs.
tank heating/tank : 9 kW
pump capacity : 2,2 kW/tank
water circulation : 900 ltrs./min.
obere Wascharme : 6
bottom washarms : 5

treble washing system

duo-plus rinse pump : 0,18 kW
consumption : 360 l/hr.
regeneration : 160 l/hr.
rinse temperature : 82-87°C
circulation temperature : 60-70°C
top rinse nozzles : 7
botto, rinse nozzles : 7

circulation nozzles top : 7
circulation nozzles bottom : 7
circulation pump : 0,55 kW#
capacity circulation-
pump : 1200 l/hr.
tank volume : 20 ltrs.

rinse booster for
treble rinse system:

electric heating

booster capacity
(coldwater-inlet) : 18 kW
booster volume : 20 l

dry zone DS and exit zone Nr. 8 :

module length dry zone : 1400 mm
free exit zone : 1400 mm
unloading height : 920 mm
heating capacity : 6 kW
ventilator : 1,95 kW
temperature : 50-55°C
air volume : 2200 m3/hr.
relative air humidity : 20 %

energy recovery system :

heat exchange : air into water
cooling surface : 25 m2
exhaust ventilator : 0,10 kW
exhaust volume : 1000 m3/hr.
temperature : 35°C
relative air humidity : 90 - 98 %
heat recovery system : approx 13 kW

included in price :

- cladding at rear side
- door insulation
- Autotimer
- conveyor start-stop switch (start of conveyor)
- check valve 3/4" for cold and
warmwater-intake
- 2 split points between pre- and
1. washing zone and between rinse
and dry zone
- main switch