

HM 081



heated banquet trolley
Isselbaecher
HM 081

Dimensions : 520 x 720 x 1000 mm
connection : 1,0 kW - 230/1/50

- 1 compartment for 8 x GN 1/1
- for up to 16 plates on wire shelves 260 mm dia.
- double wall, insulated
- statical heating
- electronic temperature control
- with 4 casters
- 2 with brakes

accessories:
2 wire shelves GN 1/1, chrome plated

execution : stainless steel

HM 048



heated banquet trolley
Isselbaecher
HM 048

Dimensions : 880 x 825 x 1040 mm
connection : 0,75 kW - 230/1/50

- 1 compartment for 16 x GN 1/1 or 8 x GN 2/1
- for up to 48 plates on wire shelves or plate rack, diam. 260 mm or 32 plates diam. 320 mm
- double wall, insulated
- statical heating
- electronic temperature control
- with 4 casters
- 2 with brakes

accessories:
2 wire shelves GN 2/1, chrome plated

execution : stainless steel

HM 096



heated banquet trolley
Isselbaecher
HM 096

Dimensions : 880 x 825 x 1790 mm
connection : 1,5 kW - 230/1/50

- 1 compartment for 32 x GN 1/1 or 16 x GN 2/1
- for up to 96 plates on wire shelves or plate rack, diam. 260 mm or 64 plates diam. 320 mm
- 2 half doors
- double wall, insulated
- statical heating
- electronic temperature control
- with 4 casters
- 2 with brakes

accessories:
4 wire shelves GN 2/1, chrome plated

execution : stainless steel

HM 128






heated banquet trolley
Isselbaecher
HM 128

Dimensions : 1130 x 825 x 1790 mm
connection : 2,25 kW - 230/1/50

- 2 compartments stacked for 32 x GN 1/1 or 16 x GN 2/1
- for up to 128 plates on wire shelves or plate rack, diam. 260 mm or 96 plates diam. 320 mm
- double wall, insulated
- statical heating
- electronic temperature control
- with 4 casters
- 2 with brakes

accessories:

	4 wire shelves GN 2/1, chrome plated execution : stainless steel
HM 192 	heated banquet trolley Isselbaecher HM 192 Dimensions : 1710 x 825 x 1790 mm connection : 3,0 KW - 230/1/50 - 2 compartments for 64 x GN 1/1 or 32 x GN 2/1 - for up to 192 plates on wire shelves or plate rack, diam. 260 mm or 128 plates diam. 320 mm - 2 x 2 half doors - double wall, insulated - statical heating - electronic temperature control - with 6 casters 2 with brakes accessories: 4 wire shelves GN 2/1, chrome plated execution : stainless steel
HC 061 M 	heated banquet trolley Isselbaecher HC 061 M Dimensions : 850 x 725 x 970 mm connection : 3,2 kW - 230/1/50 can also be used for regenerating - 1 compartment for 6 x GN 1/1 - for up to 12 plates on wire shelves or 8 plates diam. 260 mm on plate rack - double wall, insulated - forced air heating - electronic temperature control i. e. 30-90° for warm holding, 30-160°C for regenerating - timer - moisture control - with 4 casters 2 with brakes execution : stainless steel
HC 061 E 	heated banquet trolley Isselbaecher HC 061 E Dimensions : 850 x 725 x 970 mm connection : 3,2 kW - 230/1/50 can also be used for regenerating - 1 compartment for 6 x GN 1/1 - for up to 12 plates on wire shelves or 8 plates diam. 260 mm on plate rack - double wall, insulated - forced air heating - electronic temperature control, programmable i. e. 30-90° for warm holding, 30-160°C for regenerating - timer - moisture control - with 4 casters 2 with brakes execution : stainless steel

HC 101 M



heated banquet trolley
Isselbaecher
HC 101 M

Dimensions : 850 x 725 x 1270 mm
connection : 6,5 kW - 400/3/50

can also be used for regenerating

- 1 compartment for 10 x GN 1/1
- for up to 20 plates on wire shelves or 16 plates diam. 260 mm on plate rack
- double wall, insulated
- forced air heating
- electronic temperature control i. e. 30-90° for warm holding, 30-160°C for regenerating
- timer
- moisture control
- with 4 casters
- 2 with brakes

execution : stainless steel

HC 101 E



heated banquet trolley
Isselbaecher
HC 101 E

Dimensions : 850 x 725 x 1270 mm
connection : 6,5 kW - 400/3/50

can also be used for regenerating

- 1 compartment for 10 x GN 1/1
- for up to 20 plates on wire shelves or 16 plates diam. 260 mm on plate rack
- double wall, insulated
- forced air heating
- electronic temperature control, programmable
- i. e. 30-90° for warm holding, 30-160°C for regenerating
- timer
- moisture control
- with 4 casters
- 2 with brakes

execution : stainless steel

HC 112 M



heated banquet trolley
Isselbaecher
HC 112 M

Dimensions : 900 x 800 x 1700 mm
connection : 9,6 kW - 400/3/50

can also be used for regenerating

- 1 compartment for 20 x GN 1/1 or 10 x GN 2/1
- for up to 40 plates on wire shelves or 32 plates diam. 260 mm on plate rack
- double wall, insulated
- forced air heating
- electronic temperature control i. e. 30-90° for warm holding, 30-160°C for regenerating
- timer
- moisture control
- with 4 casters
- 2 with brakes

execution : stainless steel

HC 112 E



heated banquet trolley
Isselbaecher
HC 112 E

Dimensions : 900 x 800 x 1170 mm
connection : 9,6 kW - 400/3/50

can also be used for regenerating

- 1 compartment for 20 x GN 1/1 or 10 x GN 2/1
- for up to 40 plates on wire shelves or 32 plates diam. 260 mm on plate rack
- double wall, insulated
- forced air heating
- electronic temperature control, programmable
- i. e. 30-90° for warm holding, 30-160°C for regenerating
- timer
- moisture control
- with 4 casters
- 2 with brakes

execution : stainless steel

HC 153 M



heated banquet trolley
Isselbaecher
HC 153 M

Dimensions : 900 x 800 x 1660 mm
connection : 9,6 kW - 400/3/50

can also be used for regenerating

- 2 compartments stacked for 32 x GN 1/1 or 16 x GN 2/1
- for up to 64 plates on wire shelves or 64 plates diam. 260 mm on plate rack
- double wall, insulated
- forced air heating
- electronic temperature control
- i. e. 30-90° for warm holding, 30-160°C for regenerating
- timer
- moisture control
- with 4 casters
- 2 with brakes

execution : stainless steel

HC 153 E



heated banquet trolley
Isselbaecher
HC 153 E

Dimensions : 900 x 800 x 1660 mm
connection : 9,6 kW - 400/3/50

can also be used for regenerating

- 2 compartments stacked for 32 x GN 1/1 or 16 x GN 2/1
- for up to 40 plates on wire shelves or 32 plates diam. 260 mm on plate rack
- double wall, insulated
- forced air heating
- electronic temperature control, programmable
- i. e. 30-90° for warm holding, 30-160°C for regenerating
- timer
- moisture control
- with 4 casters
- 2 with brakes

execution : stainless steel

HC 156 M



heated banquet trolley
Isselbaecher
HC 156 M

Dimensions : 900 x 800 x 1660 mm
connection : 9,6 kW - 400/3/50

pass through model
can also be used for regenerating

- 2 compartments stacked for
32 x GN 1/1 or 16 x GN 2/1
- for up to 64 plates on wire shelves
or 64 plates diam. 260 mm
on plate rack
- double wall, insulated
- forced air heating
- electronic temperature control
i. e. 30-90° for warm holding,
30-160°C for regenerating
- timer
- moisture control
- with 4 casters
2 with brakes

execution : stainless steel

HC 156 E



heated banquet trolley
Isselbaecher
HC 156 E

Dimensions : 900 x 800 x 1660 mm
connection : 9,6 kW - 400/3/50

pass through model
can also be used for regenerating

- 2 compartments stacked for
32 x GN 1/1 or 16 x GN 2/1
- for up to 40 plates on wire shelves
or 32 plates diam. 260 mm
on plate rack
- double wall, insulated
- forced air heating
- electronic temperature control,
programmable
i. e. 30-90° for warm holding,
30-160°C for regenerating
- timer
- moisture control
- with 4 casters
2 with brakes

execution : stainless steel

HC 161 M



heated banquet trolley
Isselbaecher
HC 161 M

Dimensions : 850 x 680 x 1760 mm
connection : 6,4 kW - 400/3/50

can also be used for regenerating

- 2 compartments stacked for
16 x &N 1/1 or 600x400 mm
- for up to 32 plates on wire shelves
or 32 plates diam. 260 mm
on plate rack
- double wall, insulated
- forced air heating
- electronic temperature control
i. e. 30-90° for warm holding,
30-160°C for regenerating
- timer
- moisture control
- with 4 casters
2 with brakes

execution : stainless steel

HC 161 E



heated banquet trolley
Isselbaecher
HC 161 E

Dimensions : 850 x 680 x 1760 mm
connection : 6,4 kW - 40073/50

can also be used for regenerating

- 2 compartments stacked for
16 x GN 1/1 or 16 x 600 x 400 mm
- for up to 40 plates on wire shelves
or 32 plates diam. 260 mm
on plate rack
- double wall, insulated
- forced air heating
- electronic temperature control,
programmable
i. e. 30-90° for warm holding,
30-160°C for regenerating
- timer
- moisture control
- with 4 casters
2 with brakes

execution : stainless steel

HC 162 M



heated banquet trolley
Isselbaecher
HC 162 M

Dimensions : 900 x 890 x 1860 mm
connection : 9,6 kW - 400/3/50

can also be used for regenerating

- 2 compartments stacked for
16 x GN 2/1
- for up to 64 plates on wire shelves
or 88 plates diam. 260 mm
on plate rack
- double wall, insulated
- forced air heating
- electronic temperature control
i. e. 30-90° for warm holding,
30-160°C for regenerating
- timer
- moisture control
- with 4 casters
2 with brakes

execution : stainless steel

HC 162 E



heated banquet trolley
Isselbaecher
HC 162 E

Dimensions : 900 x 890 x 1860 mm
connection : 9,6 kW - 400/3/50

can also be used for regenerating

- 2 compartments stacked for
16 x GN 2/1
- for up to 64 plates on wire shelves
or 88 plates diam. 260 mm
on plate rack
- double wall, insulated
- forced air heating
- electronic temperature control,
programmable
i. e. 30-90° for warm holding,
30-160°C for regenerating
- timer
- moisture control
- with 4 casters
2 with brakes

execution : stainless steel

HD 122



refrigerated banquet trolley
Isselbaecher
HD 122

Dimensions : 820 x 850 x 1975 mm
connection : 0,9 kW - 230/1/50

- 1 compartment for 26 x GN 1/1 or 13 x GN 2/1
- for up to 52 plates on wire shelves or 26 plates diam. 260 mm on plate rack
- double wall, insulated
- forced air cooling
- electronic temperature control with defrost program,
- temperature range =°C/+5°C
- with 4 casters
- 2 with brakes

execution : stainless steel

HD 123



refrigerated banquet trolley
Isselbaecher
HD 123

Dimensions : 820 x 850 x 1975 mm
connection : 0,9 kW - 230/1/50

- 2 compartments stacked for 26 x GN 1/1 or 13 x GN 2/1
- for up to 52 plates on wire shelves or 26 plates diam. 260 mm on plate rack
- double wall, insulated
- forced air cooling
- electronic temperature control with defrost program,
- temperature range =°C/+5°C
- with 4 casters
- 2 with brakes

execution : stainless steel

HR 122



banquet trolley for deep freezing
Isselbaecher
HR 122

Dimensions : 820 x 850 x 1975 mm
connection : 0,9 kW - 230/1/50

- 1 compartment for 26 x GN 1/1 or 13 x GN 2/1
- for up to 52 plates on wire shelves or 26 plates diam. 260 mm on plate rack
- double wall, insulated
- forced air cooling
- electronic temperature control with defrost program,
- temperature range +5°C/-12°C
- with 4 casters
- 2 with brakes

execution : stainless steel





HR 122



banquet trolley for deep freezing
Isselbaecher
HR 122

Dimensions : 820 x 850 x 1975 mm
connection : 0,9 kW - 230/1/50

- 1 compartment for 26 x GN 1/1 or 13 x GN 2/1
- for up to 52 plates on wire shelves or 26 plates diam. 260 mm on plate rack
- double wall, insulated
- forced air cooling
- electronic temperature control with defrost program,
- temperature range +5°C/-12°C
- with 4 casters
- 2 with brakes

	execution : stainless steel
HR 123 	banquet trolley for deep freezing Isselbaecher HR 123 Dimensions : 820 x 850 x 1975 mm connection : 0,9 kW - 230/1/50 - 2 compartments stacked for 20 x GN 1/1 or 10 x GN 2/1 - for up to 40 plates on wire shelves or 32 plates diam. 260 mm on plate rack - double wall, insulated - forced air cooling - electronic temperature control with defrost program, - temperature range +5°C/-12°C - with 4 casters 2 with brakes execution : stainless steel
BW 11 	heated banquet trolley Isselbaecher BW 11 Dimensions : 836 x 932 x 1778 mm connection : 2,2 kW - 230/1/50 - 1 compartment with 11 pair of rails distance 115 mm, for max. 11 GN 2/1 -65 mm - double wall, insulated - heated by circulated air - electronic temperature control with digital nominal/actual - display up to 90° adjustable - movable with 4 swivel casters, of which 2 with brakes execution : stainless steel
BW 18 	heated banquet trolley Isselbaecher BW 18 Dimensions : 836 x 932 x 1873 mm connection : 2,2 kW - 230/1/50 - 1 compartment with 18 pair of rails distance 76 mm, for max. 18 GN 2/1 -65 mm - double wall, insulated - heated by circulated air - electronic temperature control with digital nominal/actual - display up to 90° adjustable - movable with 4 swivel casters, of which 2 with brakes execution : stainless steel
BW 22 	heated banquet trolley Isselbaecher BW 22 Dimensions : 1307 x 932 x 1788 mm connection : 2,2 kW - 230/1/50 - 2 compartments with 11 pair of rails distance 115 mm, max. 10 wire shelves 1084 x 650 mm without middle wall or max. 22 GN containers 2/1-100 with intermediate wall - movable with 4 swivel casters, of which 2 with brakes execution : stainless steel

banquet trolley

Isselbaecher
kitchen equipment GmbH

BW 36



heated banquet trolley
Isselbaecher
BW 36

Dimensions : 1307 x 932 x 1883 mm
connection : 2,2 kW - 230/1/50

- 19 pair of rails
- distance : 75 mm,
- max. 17 wire shelves 1084 x 650 mm, without intermediate wall or max. 36 GN containers 2/1 with middlewall
- movable with 4 swivel casters, of which 2 with brakes

execution : stainless steel

BW-UK 10



refrigerated banquet trolley
Isselbaecher
BW-UK 10

Dimensions : 836 x 932 x 1816 mm
connection : 0,8 kW - 230/1/50

- 1 compartment with 10 pair of rails distance 115 mm, for max. 10 GN 2/1 -100 mm
- double wall, insulated
- refrigerated by forced air
- electronic temperature control with digital nominal/actual - display adjustable from +8°C down to -10°C
- movable with 4 swivel casters, of which 2 with brakes

execution : stainless steel

BW-UK 15



refrigerated banquet trolley
Isselbaecher
BW-UK 15

Dimensions : 836 x 932 x 1796 mm
connection : 0,8 kW - 230/1/50

- 1 compartment with 15 pair of rails distance 75 mm, for max. 15 GN 2/1 -65 mm
- double wall, insulated
- refrigerated by forced air
- electronic temperature control with digital nominal/actual - display adjustable from +8°C down to -10°C
- movable with 4 swivel casters, of which 2 with brakes

execution : stainless steel

BW-UK 10



refrigerated banquet trolley
Isselbaecher
BW-UK 10

Dimensions : 836 x 932 x 1816 mm
connection : 0,8 kW - 230/1/50

- 1 compartment with 10 pair of rails distance 115 mm, for max. 10 GN 2/1 -100 mm
- double wall, insulated
- refrigerated by forced air
- electronic temperature control with digital nominal/actual - display adjustable from +8°C down to -10°C
- movable with 4 swivel casters, of which 2 with brakes

execution : stainless steel

BKW 1/14L


heated banquet trolley
Isselbaeher
BKW 1/14L

Dimensions : 588 x 722 x 1257 mm
connection : 1,6 KW - 230/1/50

- 1 compartment with 14 pair of rails
distance 57,5 mm, for max.
14 GN 1/1
- double wall, insulated
- heated by circulated air
- stepless temperature control
+30/+90°C
- removable cooling machine with
moisturing basin
- hinged doors to be opened up to 270°
- 4 vertical handles for
easy transport
- movable with 2 fixed and
2 swivel casters, with brakes
diam. 125 mm

execution : stainless steel

BKW 1/20L


heated banquet trolley
Isselbaeher
BKW 1/20L

Dimensions : 588 x 722 x 1602 mm
connection : 1,6 KW - 230/1/50

- 1 compartment with 20 pair of rails
distance 57,5 mm, for max.
20 GN 1/1
- double wall, insulated
- heated by circulated air
- stepless temperature control
+30/+90°C
- removable cooling machine with
moisturing basin
- hinged doors to be opened up to 270°
- 4 vertical handles for
easy transport
- movable with 2 fixed and
2 swivel casters, with brakes
diam. 125 mm

execution : stainless steel

BKW 1/14L-GN+5 PK


heated banquet trolley
Isselbaeher
BKW 1/14L-GN+PK 5

Dimensions : 588 x 721 x 1794 mm
connection : 1,6 KW - 230/1/50

- 1 compartment with 14 pair of rails
distance 57,5 mm, for max.
14 GN 1/1
- in stacked unit additional 5 pair of
rails, distance 4 x 72 mm
+ 1 x eutectic board (not
included in unit)
- double wall, insulated
- heated by circulated air
- stepless temperature control
+30/+90°C
- removable cooling machine with
moisturing basin
- hinged doors to be opened up to 270°
- 4 vertical handles for
easy transport
- movable with 2 fixed and
2 swivel casters, with brakes
diam. 125 mm

execution : stainless steel

BKW 1/36B



heated banquet trolley
Isselbaecher
BKW 1/36B

Dimensions : 793 x 842 x 1517 mm
connection : 1,6 KW - 230/1/50

- 1 compartment with 36 pair of rails
distance 57,5 mm, for max.
36 GN 1/1 or 18 x GN 2/1
- double wall, insulated
- heated by circulated air
- stepless temperature control
+30/+90°C
- removable cooling machine with
moisturing basin
- hinged doors to be opened up to 270°
- 4 vertical handles for
easy transport
- movable with 2 fixed and
2 swivel casters, with brakes
diam. 160 mm

execution : stainless steel

BKW 1/40 B



refrigerated banquet trolley
Isselbaecher
BKW 1/40 B

Dimensions : 793 x 842 x 1821 mm
connection : 0,4 kW - 230/1/50

- 1 compartment with 40 pair of rails
distance 57,5 mm, for max.
40 GN 1/1 or 20 x GN 2/1
- double wall, insulated
- refrigerated by forced air
- stepless temperature control
-2/+8°
- removable cooling machine with
moisturing basin
- hinged doors to be opened up to 270°
- 4 vertical handles for
easy transport
- movable with 2 fixed and
2 swivel casters, with brakes
diam. 160 mm

execution : stainless steel