

	beverage dispenser
CI 4 	beverage dispenser, insulated Isselbaecher CI 4 Dimensions : Ø237 x x 346 mm capacity : 4 ltrs. - stackable - isolated - protected against spillage - can be used in dish washers execution: protection case and interior basin made of s/s
CI 6 	beverage dispenser, insulated Isselbaecher CI 6 Dimensions : Ø237 x x 405 mm capacity : 6 ltrs. - stackable - isolated - protected against spillage - can be used in dish washers execution: protection case and interior basin made of s/s
CI 8 	beverage dispenser, insulated Isselbaecher CI 8 Dimensions : Ø252 x x 436 mm capacity : 8 ltrs. - stackable - isolated - protected against spillage - can be used in dish washers execution: protection case and interior basin made of s/s
CI 10 	beverage dispenser, insulated Isselbaecher CI 10 Dimensions : Ø252 x x 489 mm capacity : 10 ltrs. - stackable - isolated - protected against spillage - can be used in dish washers execution: protection case and interior basin made of s/s
CI 12 	beverage dispenser, insulated Isselbaecher CI 12 Dimensions : Ø307 x x 427 mm capacity : 12 ltrs. - stackable - isolated - protected against spillage - can be used in dish washers execution: protection case and interior basin made of s/s
CI 16 	beverage dispenser, insulated Isselbaecher CI 16 Dimensions : Ø307 x x 504 mm capacity : 16 ltrs. - stackable - isolated - protected against spillage - can be used in dish washers execution: protection case and interior basin made of s/s

<p>CI 20</p> 	<p>beverage dispenser, insulated Isselbaecher CI 20</p> <p>Dimensions : Ø307 x x 576 mm capacity : 20 ltrs. - stackable - isolated - protected against spillage - can be unsed in dish washers</p> <p>execution: protection case and interior basin made of s/s</p>
<p>CI 25</p> 	<p>beverage dispenser, insulated Isselbaecher CI 25</p> <p>Dimensions : Ø307 x x 655 mm capacity : 25 ltrs. - stackable - isolated - protected against spillage - can be unsed in dish washers</p> <p>execution: protection case and interior basin made of s/s</p>
<p>CN5i</p> 	<p>beverage dispenser, insulated Isselbaecher CN5i</p> <p>Dimensions : x Ø237 x 406 mm - content : 5 ltrs. - isolated - incl. show glass and no drip tap - stackable - with isolated lid - can be unsed in dish washers</p> <p>Acc: coffee mixer with show glass</p>
<p>CN5i-99</p> 	<p>beverage dispenser, insulated Isselbaecher CN5i-99</p> <p>Dimensions : x Ø237 x 406 mm - content : 5 ltrs. - isolated - incl. no-drip-tap - stackable - with isolated lid - can be unsed in dish washers</p> <p>accessories : coffee mixer</p>
<p>CN10i</p> 	<p>beverage dispenser, insulated Isselbaecher CN10i</p> <p>Dimensions : x Ø237 x 406 mm - content : 10 ltrs. - isolated - incl. show glass and no drip tap - stackable - with isolated lid - can be unsed in dish washers</p> <p>Acc: coffee mixer with show glass</p>
<p>CN10i-99</p> 	<p>beverage dispenser, insulated Isselbaecher CN10i-99</p> <p>Dimensions : x Ø237 x 406 mm - content : 10 ltrs. - isolated - incl. no-drip-tap - stackable - with isolated lid - can be unsed in dish washers</p> <p>accessories : coffee mixer</p>

CN20i



beverage dispenser, insulated
Isselbaecher
CN20i

Dimensions : x Ø237 x 406 mm
- content : 20 ltrs.
- isolated
- incl. show glass and no drip tap
- stackable
- with isolated lid
- can be used in dish washers

Acc: coffee mixer with show glass

CN20i-99



beverage dispenser, insulated
Isselbaecher
CN20i-99

Dimensions : x Ø237 x 406 mm
- content : 20 ltrs.
- isolated
- incl. no-drip-tap
- stackable
- with isolated lid
- can be used in dish washers

accessories : coffee mixer

CE 4



beverage dispenser, heated
Isselbaecher
CE 4

Dimensions : Ø237 x x 346 mm
connection : 0,17 kW - 230/1/50-60

capacity : 4 ltrs.
stackable,
- thermostatically controlled
warming temperature
- indirect circulated air heating

execution: protection case and interior
basin made of s/s

CE 6



beverage dispenser, heated
Isselbaecher
CE 6

Dimensions : Ø237 x x 410 mm
connection : 0,17 kW - 230/1/50-60

capacity : 6 ltrs.
stackable,
- thermostatically controlled
warming temperature
- indirect circulated air heating

execution: protection case and interior
basin made of s/s

CE 8



beverage dispenser, heated
Isselbaecher
CE 8

Dimensions : Ø252 x x 440 mm
connection : 0,17 kW - 230/1/50-60

capacity : 8 ltrs.
stackable,
- thermostatically controlled
warming temperature
- indirect circulated air heating

execution: protection case and interior
basin made of s/s

<p>CE 10</p> 	<p>beverage dispenser, heated Isselbaecher CE 10</p> <p>Dimensions : Ø252 x x 489 mm connection : 0,17 kW - 230/1/50-60</p> <p>capacity : 10 ltrs. stackable, - thermostatically controlled warming temperature - indirect circulated air heating</p> <p>execution: protection case and interior basin made of s/s</p>
<p>CE 12</p> 	<p>beverage dispenser, heated Isselbaecher CE 12</p> <p>Dimensions : Ø307 x x 427 mm connection : 0,28 kW - 230/1/50-60</p> <p>capacity : 12 ltrs. stackable, - thermostatically controlled warming temperature - indirect circulated air heating</p> <p>execution: protection case and interior basin made of s/s</p>
<p>CE 16</p> 	<p>beverage dispenser, heated Isselbaecher CE 16</p> <p>Dimensions : Ø307 x x 504 mm connection : 0,28 kW - 230/1/50-60</p> <p>capacity : 16 ltrs. stackable, - thermostatically controlled warming temperature - indirect circulated air heating</p> <p>execution: protection case and interior basin made of s/s</p>
<p>CE 20</p> 	<p>beverage dispenser, heated Isselbaecher CE 20</p> <p>Dimensions : Ø307 x x 576 mm connection : 0,39 kW - 230/1/50-60</p> <p>capacity : 20 ltrs. stackable, - thermostatically controlled warming temperature - indirect circulated air heating</p> <p>execution: protection case and interior basin made of s/s</p>
<p>CE 25</p> 	<p>beverage dispenser, heated Isselbaecher CE 25</p> <p>Dimensions : Ø307 x x 655 mm connection : 0,39 kW - 230/1/50-60</p> <p>capacity : 25 ltrs. stackable, - thermostatically controlled warming temperature - indirect circulated air heating</p> <p>execution: protection case and interior basin made of s/s</p>

CN5e




beverage dispenser, heated
Isselbaecher
CN5e

Dimensions : x Ø237 x 406 mm
connection : 0,035 kW - 230/1/50-50

- content : 5 ltrs.
- heated
- incl. show glass and no drip tap
- stackable
- with isolated lid

Acc: coffee mixer with show glass

CN5e-99



beverage dispenser, heated
Isselbaecher
CN5e-99

Dimensions : x Ø237 x 406 mm
connection : 0,035 kW - 230/1/50-50

- content : 5 ltrs.
- heated
- incl. no-drip-tap
- stackable
- with isolated lid

accessories : coffee mixer

CN10e




beverage dispenser, heated
Isselbaecher
CN10e

Dimensions : x Ø307 x 427 mm
connection : 0,07 kW - 230/1/50-60

- content : 10 ltrs.
- heated
- incl. show glass and no drip tap
- stackable
- with isolated lid

Acc: coffee mixer with show glass

CN10e-99



beverage dispenser, heated
Isselbaecher
CN10e-99

Dimensions : x Ø307 x 427 mm
connection : 0,07 kW - 230/1/50-60

- content : 10 ltrs.
- heated
- incl. no-drip-tap
- stackable
- with isolated lid

accessories : coffee mixer

CN20e



beverage dispenser, heated
Isselbaecher
CN20e

Dimensions : x Ø355 x 515 mm
connection : 0,07 kW - 230/1/50-60

- content : 20 ltrs.
- heated
- incl. show glass and no drip tap
- stackable
- with isolated lid

Acc: coffee mixer with show glass

<p>CN20e-99</p> 	<p>beverage dispenser, heated Isselbaecher CN20e-99</p> <p>Dimensions : x Ø355 x 515 mm connection : 0,07 kW - 230/1/50-60</p> <ul style="list-style-type: none"> - content : 20 ltrs. - heated - incl. no-drip-tap - stackable - with isolated lid <p>accessories : coffee mixer</p>
<p>VHG 10</p> 	<p>beverage dispenser, heated Bonamat VHG 10</p> <p>Dimensions : x x 464 mm connection : 0,09 kW - 230/1/50</p> <ul style="list-style-type: none"> - content : 10 ltrs. - electrical heating - diam. 286 mm - liquid level indicator - no-drip-tap - double walled <p>execution : stainless steel</p>
<p>VHG 20</p> 	<p>beverage dispenser, heated Bonamat VHG 20</p> <p>Dimensions : x x 510 mm connection : 0,12 kW - 230/1/50</p> <ul style="list-style-type: none"> - content : 20 ltrs. - electrical heating - diam. 374 mm - liquid level indicator - no-drip-tap - double walled <p>execution : stainless steel</p>
<p>VHG 40</p> 	<p>beverage dispenser, heated Bonamat VHG 40</p> <p>Dimensions : x x 629 mm connection : 0,16 kW - 230/1/50</p> <ul style="list-style-type: none"> - content : 40 ltrs. - electrical heating - diam. 423 mm - liquid level indicator - no-drip-tap - double walled <p>execution : stainless steel</p>
<p>85040102</p> 	<p>beverage dispenser, heated Rieber 85040102</p> <p>Dimensions : 219 x 368 x 4354 mm connection : 0,1 kW - 230/1/50</p> <p>content : 12 ltrs. lid and container double walled with FCKW free PU 30 mm insulated deep drawn int. container with ext. coat seamlessly welded container and lid with 2 tension locks, lockable drain tap made of black plastics heating thermostatically locked.</p> <p>accessories : 1 connecting cable, 2 m length</p> <p>execution : stainless steel</p>

85040103



beverage dispenser, heated
Rieber
85040103

Dimensions : 219 x 368 x 5352 mm
connection : 0,1 kW - 230/1/50

content : 16 ltrs.
lid and container double walled with
FCKW free PU 30 mm insulated
deep drawn int. container with
ext. coat seamlessly welded
container and lid with 2 tension
locks, lockable
drain tap made of black plastics
heating thermostatically
locked.
accessories :
1 connecting cable, 2 m length

execution : stainless steel

85040104



beverage dispenser, heated
Rieber
85040104

Dimensions : 219 x 368 x 7357 mm
connection : 0,1 kW - 230/1/50

content : 24 ltrs.
lid and container double walled with
FCKW free PU 30 mm insulated
deep drawn int. container with
ext. coat seamlessly welded
container and lid with 2 tension
locks, lockable
drain tap made of black plastics
heating thermostatically
locked.
accessories :
1 connecting cable, 2 m length

execution : stainless steel