

forced-air cold pans

Isselbaecher
kitchen equipment GmbH

HUW 2G3 	forced-air cold pans Isselbaecher HUW 2G3 Dimensions : 765 x 665 x 700 mm connection : 0,35 KW - 230/1/50 dim. of cut-out : 740 x 690 mm inner dim. : 655 x 560 x 205 mm - GN 2 x 1/1 - circulating air refig.bowl stainless steel - main switch - digital temperature display - alarm function with emergency mode - temperature adjustable - cooling machine, substructure - automatic defrost
HUW 3G3 	forced-air cold pans Isselbaecher HUW 3G3 Dimensions : 1085 x 710 x 700 mm connection : 0,45 kW - 230/1/50 dim. of cut-out : 1065 x 690 mm inner dim. : 980 x 560 x 205 mm - GN 3 x 1/1 - circulating air refig.bowl stainless steel - main switch - digital temperature display - alarm function with emergency mode - temperature adjustable - cooling machine, substructure - automatic defrost
HUW 4G3 	forced-air cold pans Isselbaecher HUW 4G3 Dimensions : 1410 x 710 x 700 mm connection : 0,5 kW - 230/1/50 dim. of cut-out : 1390 x 690 mm inner dim. : 1305 x 560 x 205 mm - GN 4 x 1/1 - circulating air refig.bowl stainless steel - main switch - digital temperature display - alarm function with emergency mode - temperature adjustable - cooling machine, substructure - automatic defrost
HUW 5G3 	forced-air cold pans Isselbaecher HUW 5G3 Dimensions : 1735 x 710 x 700 mm connection : 0,6 kW - 230/1/50 dim. of cut-out : 1715 x 690 mm inner dim. : 1630 x 560 x 205 mm - GN 5 x 1/1 - circulating air refig.bowl stainless steel - main switch - digital temperature display - alarm function with emergency mode - temperature adjustable - cooling machine, substructure - automatic defrost