

# Disinfection Spray Unit

**Isselbaecher**  
kitchen equipment GmbH

Topmater J 20-2P-CA



spray disinfectant cleaner  
Isselbaecher  
Topmater J 20-2P-CA

Dimensions : 271 x 132 x 395 mm  
wall installation  
consisting of:

- rear side of housing with sprayhose bracket for wall installation
- housing cover made of impact-proof plastics
- pipe disconnecter CA 225
- 1 freshwater cut-off cock
- 1 injector mixing valve
- 1 switch lever

"product/rinsing"

- 1 switch lever selection

product 1 or product 2

- 2 suction hoses 1m with foot valve
- 1 connecting hose 1/2" length 1,5 m
- 1 set of dosing nozzles
- 2 container holders made of s/s for 5/10 l containers
- 1 spray hose 1/2" length 20 m with 3/4" nut
- 1 self-closing, heat insulated spray gun
- mounting material
- flow up to 650 l/hr.
- suction lift up to max. 1,5 m
- for connection to cord- or warm water up to max. 40°C
- water flow pressure 2,0-6,9 bar max.

Topmater J 20-2P-BA



spray disinfectant cleaner  
Isselbaecher  
Topmater J 20-2P-BA

Dimensions : 271 x 118 x 394 mm  
wall installation  
consisting of:

- rear side of housing with sprayhose bracket for wall installation
- housing cover made of impact-proof plastics
- pipe disconnecter BA 195
- 1 freshwater cut-off cock
- 1 injector mixing valve
- 1 switch lever

"product/rinsing"

- 1 switch lever selection

product 1 or product 2

- 2 suction hoses 1m with foot valve
- 1 connecting hose 1/2" length 1,5 m
- 1 set of dosing nozzles
- 2 container holders made of s/s for 5/10 l containers
- 1 spray hose 1/2" length 20 m with 3/4" nut
- 1 self-closing, heat insulated spray gun
- mounting material
- flow up to 650 l/hr.
- suction lift up to max. 1,5 m
- for connection to cord- or warm water up to max. 40°C
- water flow pressure 3,0-6,0 bar max.

Topmater J 40-2P-BA+



spray disinfectant cleaner  
Isselbaecher  
Topmater J 40-2P-BA+KIT

Dimensions : 320 x 170 x 700 mm  
wall installation

consisting of:

- rear side of housing with sprayhose bracket for wall installation
- housing cover made of impact-proof plastics
- pipe disconnecter BA 270
- 1 dirt filter
- 1 freshwater cut-off cock
- 1 dispensing pump

- 1 switch lever  
"product/rinsing"
- 1 switch lever selection  
product 1 or product 2
- 2 suction hoses 1m with foot valve
- 1 connecting hose 1/2" length 1,5 m
- 2 container holders made of s/s for  
5/10 l containers
- 1 spray hose 1/2" length 20 m  
with 3/4" nut
- 1 self-closing,  
heat insulated spray gun
- mounting material
- flow min. 50 l/hr.  
up to max. 1500 l/hr.
- suction lift up to max. 1,0 m
- for connection to cord- or  
warm water up to max. 40°C
- water flow pressure 3,0-6,0 bar max.
- dosing range 0,2 - 2 %
- dosing operation :  
hydraulic dosing pump  
dosing to be changed by  
adjusting piston