

Roll-In 1PP TN



roll-through refrigerator
Isselbaecher
ROLL-IN 1PP TN

Dimensions : 880 x 1020 x 2180 mm
connection : 0,52 kW - 230/1/50

- GN 2/1
- insulation : 80 mm
- temperature range: +2/+10°C
- with thermostic control
- with 1 door with handle strip at front side
- with 1 door with handle strip at rear
- cooling machine on top by circulated air evaporator with automatic evaporation, incl. thaw water tray for manual discharge,

execution: interior and exterior
stainless steel

Roll-In 1PPV TN



roll-through refrigerator
Isselbaecher
ROLL-IN 1PPV TN

Dimensions : 880 x 1020 x 2180 mm
connection : 0,52 kW - 230/1/50

- GN 2/1
- insulation : 80 mm
- temperature range: +2/+10°C
- with thermostic control
- with 1 glass door with handle at front side
- with 1 glass door with handle at rear
- cooling machine on top by circulated air evaporator with automatic evaporation, incl. thaw water collecting pan for manual discharge,

execution: interior and exterior
stainless steel

Roll-In 2PP TN



roll-through refrigerator
Isselbaecher
ROLL-IN 2PP TN

Dimensions : 1760 x 1020 x 2180 mm
connection : 0,52 kW - 230/1/50

- GN 2/1
- insulation : 80 mm
- temperature range: +2/+10°C
- with thermostic control
- with 2 doors with handle at front side
- with 2 doors with handle at rear
- cooling machine on top by circulated air evaporator with automatic evaporation, incl. thaw water collecting pan for manual discharge,

execution: interior and exterior
stainless steel

Roll-In 2PPV TN



roll-through refrigerator
Isselbaecher
ROLL-IN 2PPV TN

Dimensions : 1760 x 1020 x 2180 mm
connection : 0,52 kW - 230/1/50

- GN 2/1
- insulation : 80 mm
- temperature range: +2/+10°C
- with thermostic control
- with 2 glass doors with handle at front side
- with 2 glass doors with handle at rear

- cooling machine on top by circulated air
evaporator with automatic
evaporation,
incl. thaw water collecting pan for
manual discharge,

execution: interior and exterior
stainless steel