exhaust hood		Isselbaecher kitchen equipment GmbH
	WALL TYPE HOOD, depth 900 mm	
WH-900-750	exhaust hood (wall type) Isselbaecher	
	Dimensions: 750 x 900 x 500 mm connection: 0,02 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-900-800	exhaust hood (wall type) Isselbaecher	
	Dimensions: 800 x 900 x 500 mm connection: 0,02 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-900-900	exhaust hood (wall type) Isselbaecher	
	Dimensions: 900 x 900 x 500 mm connection: 0,02 kW - 220/1/50	
	hood housing with ambient grease- collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-900-1000	exhaust hood (wall type) Isselbaecher	
	Dimensions: 1000 x 900 x 500 mm connection: 0,02 kW - 220/1/50	
	hood housing with ambient grease- collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-900-1200	exhaust hood (wall type) Isselbaecher	
	Dimensions : 1200 x 900 x 500 mm connection : 0,02 kW - 220/1/50	
	hood housing with ambient grease- collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

exhaust hood		Isselbaecher kitchen equipment GmbH
WH-900-1400	exhaust hood (wall type) Isselbaecher	
	Dimensions : 1400 x 900 x 500 mm connexion : 0,04 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-900-1600	exhaust hood (wall type) Isselbaecher	
	Dimensions : 1600 x 900 x 500 mm connexion : 0,04 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-900-1800	exhaust hood (wall type) Isselbaecher	
	Dimensions : 1800 x 900 x 500 mm connection : 0,06 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-900-2000	exhaust hood (wall type) Isselbaecher	
	Dimensions : 2000 x 900 x 500 mm connection : 0,06 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-900-2200	exhaust hood (wall type) Isselbaecher	
	Dimensions : 2200 x 900 x 500 mm connection : 0,06 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

exhaust hood		Isselbaecher kitchen equipment GmbH
WH-900-2400	exhauste hood (wall type) in 2 parts Isselbaecher	
	Dimensions : 2400 x 900 x 500 mm connection : 0,06 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-900-2600	exhauste hood (wall type) in 2 parts Isselbaecher	
	Dimensions : 2600 x 900 x 500 mm connection : 0,06 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-900-2800	exhauste hood (wall type) in 2 parts Isselbaecher	
	Dimensions: 2800 x 900 x 500 mm connection: 0,06 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-900-3000	exhauste hood (wall type) in 2 parts Isselbaecher	
	Dimensions : 3000 x 900 x 500 mm connection : 0,07 kW - 230/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-900-3200	exhauste hood (wall type) in 2 parts Isselbaecher	
	Dimensions : 3200 x 900 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

exhaust hood		Isselbaecher kitchen equipment GmbH
WH-900-3400	exhauste hood (wall type) in 2 parts Isselbaecher	
	Dimensions: 3400 x 900 x 500 mm connection: 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-900-3600	exhauste hood (wall type) in 2 parts Isselbaecher	
	Dimensions : 3600 x 900 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease- collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-900-3800	exhauste hood (wall type) in 2 parts Isselbaecher	
	Dimensions: 3800 x 900 x 500 mm connection: 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-900-4000	exhauste hood (wall type) in 2 parts Isselbaecher	
	Dimensions: 4000 x 900 x 500 mm connection: 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-900-4200	exhaust hood (wall type) in 3 parts Isselbaecher	
	Dimensions: 4200 x 900 x 500 mm connection: 0,12 KW - 220/1/50	
	hood housing with ambient grease- collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

exhaust hood		Isselbaecher kitchen equipment GmbH
WH-900-4400	exhaust hood (wall type) in 3 parts Isselbaecher	
	Dimensions: 4400 x 900 x 500 mm connection: 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-900-4600	exhaust hood (wall type) in 3 parts Isselbaecher	
	Dimensions : 4600 x 900 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-900-4800	exhaust hood (wall type) in 3 parts Isselbaecher	
	Dimensions: 4800 x 900 x 500 mm connection: 0,12 KW - 220/1/50	
	hood housing with ambient grease- collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-900-5000	exhaust hood (wall type) in 3 parts Isselbaecher	
	Dimensions : 5000 x 900 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-900-5200	exhaust hood (wall type) in 3 parts Isselbaecher	
	Dimensions : 5200 x 900 x 500 mm Anschlusswert: 0,18 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

	kitchen equipment GmbH
exhaust hood (wall type) in 3 parts Isselbaecher	
Dimensions : 5400 x 900 x 500 mm Anschlusswert: 0,18 KW - 220/1/50	
hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
execution : stainless steel	
exhaust hood (wall type) in 3 parts Isselbaecher	
Dimensions : 5600 x 900 x 500 mm Anschlusswert: 0,18 KW - 220/1/50	
hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
execution : stainless steel	
exhaust hood (wall type) in 3 parts Isselbaecher	
Dimensions : 5800 x 900 x 500 mm Anschlusswert: 0,18 KW - 220/1/50	
hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
execution : stainless steel	
exhaust hood (wall type) in 3 parts Isselbaecher	
Dimensions : 6000 x 900 x 500 mm Anschlusswert: 0,18 KW - 220/1/50	
hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
execution : stainless steel	
WALL TYPE HOOD, depth 1200 mm	
exhaust hood (wall type) Isselbaecher	
Dimensions: 750 x 1200 x 500 mm connection: 0,02 kW - 220/1/50	
hood housing with ambient grease- collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
execution : stainless steel	
	Isselbaecher Dimensions: 5400 x 900 x 500 mm Anschlusswert: 0,18 KW - 220/1/50 hood housing with ambient grease- collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system execution: stainless steel exhaust hood (wall type) in 3 parts Isselbaecher Dimensions: 5600 x 900 x 500 mm Anschlusswert: 0,18 KW - 220/1/50 hood housing with ambient grease- collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system execution: stainless steel exhaust hood (wall type) in 3 parts Isselbaecher Dimensions: 5800 x 900 x 500 mm Anschlusswert: 0,18 KW - 220/1/50 hood housing with ambient grease- collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system execution: stainless steel exhaust hood (wall type) in 3 parts Isselbaecher Dimensions: 6000 x 900 x 500 mm Anschlusswert: 0,18 KW - 220/1/50 hood housing with ambient grease- collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust hood (wall type) in 3 parts Isselbaecher Dimensions: 6000 x 900 x 500 mm Anschlusswert: 0,18 KW - 220/1/50 hood housing with ambient grease- collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system execution: stainless steel WALL TYPE HOOD, depth 1200 mm =================================

exhaust hood		Isselbaecher kitchen equipment GmbH
WH-1200-800	exhaust hood (wall type) Isselbaecher	
	Dimensions : 800 x 1200 x 500 mm connection : 0,02 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-1200-900	exhaust hood (wall type) Isselbaecher	
	Dimensions : 900 x 1200 x 500 mm connection : 0,02 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-1200-1000	exhaust hood (wall type) Isselbaecher	
	Dimensions : 1000 x 1200 x 500 mm connection : 0,02 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-1200-1200	exhaust hood (wall type) Isselbaecher	
	Dimensions : 1200 x 1200 x 500 mm connection : 0,02 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-1200-1400	exhaust hood (wall type) Isselbaecher	
	Dimensions : 1400 x 1200 x 500 mm connexion : 0,04 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

exhaust hood		Isselbaecher kitchen equipment GmbH
WH-1200-1600	exhaust hood (wall type) Isselbaecher	
	Dimensions : 1600 x 1200 x 500 mm connexion : 0,04 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-1200-1800	exhaust hood (wall type) Isselbaecher	
	Dimensions : 1800 x 1200 x 500 mm connection : 0,06 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-1200-2000	exhaust hood (wall type) Isselbaecher	
	Dimensions : 2000 x 1200 x 500 mm connection : 0,06 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-1200-2200	exhaust hood (wall type) Isselbaecher	
	Dimensions : 2200 x 1200 x 500 mm connection : 0,06 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-1200-2400	exhauste hood (wall type) in 2 parts Isselbaecher	
	Dimensions : 2400 x 1200 x 500 mm connection : 0,06 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

exhaust hood		Isselbaecher kitchen equipment GmbH
WH-1200-2600	exhauste hood (wall type) in 2 parts Isselbaecher	
	Dimensions : 2600 x 1200 x 500 mm connection : 0,06 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-1200-2800	exhauste hood (wall type) in 2 parts Isselbaecher	
	Dimensions : 2800 x 1200 x 500 mm connection : 0,06 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-1200-3000	exhauste hood (wall type) in 2 parts Isselbaecher	
	Dimensions : 3000 x 1200 x 500 mm connection : 0,06 kW - 220/1/50	
	hood housing with ambient grease- collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-1200-3200	exhauste hood (wall type) in 2 parts Isselbaecher	
	Dimensions : 3200 x 1200 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-1200-3400	exhauste hood (wall type) in 2 parts Isselbaecher	
	Dimensions : 3400 x 1200 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

exhaust hood		Isselbaecher kitchen equipment GmbH
WH-1200-3600	exhauste hood (wall type) in 2 parts Isselbaecher	
	Dimensions : 3600 x 1200 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-1200-3800	exhauste hood (wall type) in 2 parts Isselbaecher	
	Dimensions : 3800 x 1200 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-1200-4000	exhauste hood (wall type) in 2 parts Isselbaecher	
	Dimensions : 4000 x 1200 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-1200-4200	exhaust hood (wall type) in 3 parts Isselbaecher	
	Dimensions: 4200 x 1200 x 500 mm connection: 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-1200-4400	exhaust hood (wall type) in 3 parts Isselbaecher	
	Dimensions : 4400 x 1200 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

exhaust hood		Isselbaecher kitchen equipment GmbH
WH-1200-4600	exhaust hood (wall type) in 3 parts Isselbaecher	
	Dimensions : 4600 x 1200 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-1200-4800	exhaust hood (wall type) in 3 parts Isselbaecher	
	Dimensions : 4800 x 1200 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-1200-5000	exhaust hood (wall type) in 3 parts Isselbaecher	
	Dimensions : 5000 x 1200 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-1200-5200	exhaust hood (wall type) in 3 parts Isselbaecher	
	Dimensions : 5200 x 1200 x 500 mm Anschlusswert: 0,18 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-1200-5400	exhaust hood (wall type) in 3 parts Isselbaecher	
	Dimensions : 5400 x 1200 x 500 mm Anschlusswert: 0,18 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

exhaust hood		Isselbaecher kitchen equipment GmbH
WH-1200-5600	exhaust hood (wall type) in 3 parts Isselbaecher	
	Dimensions : 5600 x 1200 x 500 mm Anschlusswert: 0,18 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
WH-1200-5800	exhaust hood (wall type) in 3 parts Isselbaecher	
	Dimensions : 5800 x 1200 x 500 mm Anschlusswert: 0,18 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
THE 1200 COO.	execution : stainless steel	
WH-1200-6000	exhaust hood (wall type) in 3 parts Isselbaecher	
	Dimensions : 6000 x 1200 x 500 mm Anschlusswert: 0,18 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
	CENTRE TYPE HOOD, depth 1800 mm	
MH-1800-1000	exhaust hood (centre type) Isselbaecher	
	Dimensions : 1000 x 1800 x 500 mm connexion : 0,04 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-1800-1200	exhaust hood (centre type) Isselbaecher	
	Dimensions : 1200 x 1800 x 500 mm connexion : 0,04 KW - 220/1/50	
E TOTAL	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

exhaust hood		Isselbaecher kitchen equipment GmbH
MH-1800-1400	exhaust hood (centre type) Isselbaecher	
	Dimensions : 1400 x 1800 x 500 mm Anschlusswert: 0,08 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-1800-1600	exhaust hood (centre type) Isselbaecher	
	Dimensions : 1600 x 1800 x 500 mm Anschlusswert: 0,08 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
W. 1000 1000	execution : stainless steel	
MH-1800-1800	exhaust hood (centre type) Isselbaecher	
	Dimensions : 1800 x 1800 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-1800-2000	exhaust hood (centre type) Isselbaecher	
	Dimensions : 2000 x 1800 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-1800-2200	exhaust hood (centre type) Isselbaecher	
4	Dimensions : 2200 x 1800 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

exhaust hood		Isselbaecher kitchen equipment GmbH
MH-1800-2400	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 2400 x 1800 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-1800-2600	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 2600 x 1800 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-1800-2800	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 2800 x 1800 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-1800-3000	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 3000 x 1800 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-1800-3200	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 3200 x 1800 x 500 mm connection : 0,12 KW - 220/1/50	
P. J. W.	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

exhaust hood		Isselbaecher kitchen equipment GmbH
MH-1800-3400	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 3400 x 1800 x 500 mm connection : 0,24 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-1800-3600	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 3600 x 1800 x 500 mm connection : 0,24 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-1800-3800	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 3800 x 1800 x 500 mm connection : 0,24 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-1800-4000	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 4000 x 1800 x 500 mm connection : 0,24 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-1800-4200	exhaust hood (centre type) in 2 parts Isselbaecher	
4	Dimensions : 4200 x 1800 x 500 mm connection : 0,24 kW - 220/1/50	
P. J. W.	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

exhaust hood		Isselbaecher kitchen equipment GmbH
MH-1800-4400	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 4400 x 1800 x 500 mm connection : 0,24 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-1800-4600	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 4600 x 1800 x 500 mm connection : 0,24 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-1800-4800	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 4800 x 1800 x 500 mm connection : 0,24 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-1800-5000	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 5000 x 1800 x 500 mm connection : 0,24 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-1800-5200	exhaust hood (centre type) in 4 parts Isselbaecher	
4	Dimensions : 5200 x 1800 x 500 mm connection : 0,36 kW - 220/1/50	
P. J. W.	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

exhaust hood		Isselbaecher kitchen equipment GmbH
MH-1800-5400	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 5400 x 1800 x 500 mm connection : 0,36 kW - 220/1/50	
L. T. T.	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-1800-5600	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 5600 x 1800 x 500 mm connection : 0,36 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-1800-5800	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 5800 x 1800 x 500 mm connection : 0,36 kW - 220/1/50	
L. T. T.	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-1800-6000	exhaust hood (centre type) in 4 parts Isselbaecher	
4	Dimensions : 6000 x 1800 x 500 mm connection : 0,36 kW - 220/1/50	
A TOTAL OF THE PARTY OF THE PAR	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
	CENTRE TYPE HOOD, depth 2000 mm	
MH-2000-1000	exhaust hood (centre type) Isselbaecher	
4	Dimensions : 1000 x 2000 x 500 mm connexion : 0,04 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

exhaust hood		Isselbaecher kitchen equipment GmbH
MH-2000-1200	exhaust hood (centre type) Isselbaecher	
	Dimensions : 1200 x 2000 x 500 mm connexion : 0,04 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2000-1400	exhaust hood (centre type) Isselbaecher	
	Dimensions: 1400 x 2000 x 500 mm Anschlusswert: 0,08 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
MH-2000-1600	execution : stainless steel	
MH-2000-1600	exhaust hood (centre type) Isselbaecher	
	Dimensions : 1600 x 2000 x 500 mm Anschlusswert: 0,08 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2000-1800	exhaust hood (centre type) Isselbaecher	
	Dimensions : 1800 x 2000 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2000-2000	exhaust hood (centre type) in 2 parts Isselbaecher	
4	Dimensions : 2000 x 2000 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

exhaust hood		Isselbaecher kitchen equipment GmbH
MH-2000-2200	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 2200 x 2000 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2000-2400	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 2400 x 2000 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2000-2600	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 2600 x 2000 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease- collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2000-2800	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 2800 x 2000 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2000-3000	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 3000 x 2000 x 500 mm connection : 0,12 KW - 220/1/50	
The state of the s	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

exhaust hood		Isselbaecher kitchen equipment GmbH
MH-2000-3200	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 3200 x 2000 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2000-3400	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 3400 x 2000 x 500 mm connection : 0,24 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2000-3600	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 3600 x 2000 x 500 mm connection : 0,24 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2000-3800	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 3800 x 2000 x 500 mm connection : 0,24 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2000-4000	exhaust hood (centre type) in 4 parts Isselbaecher	
4	Dimensions : 4000 x 2000 x 500 mm connection : 0,24 kW - 220/1/50	
P. J. III	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

exhaust hood		Isselbaecher kitchen equipment GmbH
MH-2000-4200	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 4200 x 2000 x 500 mm connection : 0,24 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2000-4400	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 4400 x 2000 x 500 mm connection : 0,24 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2000-4600	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 4600 x 2000 x 500 mm connection : 0,24 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2000-4800	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 4800 x 2000 x 500 mm connection : 0,24 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2000-5000	exhaust hood (centre type) in 4 parts Isselbaecher	
4	Dimensions : 5000 x 2000 x 500 mm connection : 0,24 kW - 220/1/50	
P. J. W.	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

exhaust hood		Isselbaecher kitchen equipment GmbH
MH-2000-5200	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 5200 x 2000 x 500 mm connection : 0,36 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2000-5400	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 5400 x 2000 x 500 mm connection : 0,36 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2000-5600	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 5600 x 2000 x 500 mm connection : 0,36 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2000-5800	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 5800 x 2000 x 500 mm connection : 0,36 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2000-6000	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 6000 x 2000 x 500 mm connection : 0,36 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
	CENTRE TYPE HOOD, depth 2200 mm	

exhaust hood		Isselbaecher kitchen equipment GmbH
MH-2200-1000	exhaust hood (centre type) Isselbaecher	
	Dimensions : 1000 x 2200 x 500 mm connexion : 0,04 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2200-1200	exhaust hood (centre type) Isselbaecher	
4	Dimensions : 1200 x 2200 x 500 mm connexion : 0,04 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2200-1400	exhaust hood (centre type) Isselbaecher	
4	Dimensions : 1400 x 2200 x 500 mm Anschlusswert: 0,08 KW - 220/1/50	
	hood housing with ambient grease- collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
мн-2200-1600	exhaust hood (centre type) Isselbaecher	
4	Dimensions : 1600 x 2200 x 500 mm Anschlusswert: 0,08 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2200-1800	exhaust hood (centre type) Isselbaecher	
	Dimensions : 1800 x 2200 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

exhaust hood		Isselbaecher kitchen equipment GmbH
MH-2200-2000	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 2000 x 2200 x 500 mm connection : 0,12 KW - 220/1/50	
N. T. S.	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2200-2200	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 2200 x 2200 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2200-2400	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 2400 x 2200 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease- collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2200-2600	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 2600 x 2200 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2200-2800	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 2800 x 2200 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

exhaust hood		Isselbaecher kitchen equipment GmbH
MH-2200-3000	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 3000 x 2200 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2200-3200	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 3200 x 2200 x 500 mm connection : 0,12 KW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2200-3400	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 3400 x 2200 x 500 mm connection : 0,24 kW - 220/1/50	
	hood housing with ambient grease- collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2200-3600	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 3600 x 2200 x 500 mm connection : 0,24 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
МН-2200-3800	exhaust hood (centre type) in 2 parts Isselbaecher	
	Dimensions : 3800 x 2200 x 500 mm connection : 0,24 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

exhaust hood		Isselbaecher kitchen equipment GmbH
MH-2200-4000	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 4000 x 2200 x 500 mm connection : 0,24 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2200-4200	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions: 4200 x 2200 x 500 mm connection: 0,24 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2200-4400	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 4400 x 2200 x 500 mm connection : 0,24 kW - 220/1/50	
A STATE OF THE STA	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2200-4600	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 4600 x 2200 x 500 mm connection : 0,24 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2200-4800	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 4800 x 2200 x 500 mm connection : 0,24 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

exhaust hood		Isselbaecher kitchen equipment GmbH
MH-2200-5000	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 5000 x 2200 x 500 mm connection : 0,24 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2200-5200	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 5200 x 2200 x 500 mm connection : 0,36 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2200-5400	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 5400 x 2200 x 500 mm connection : 0,36 kW - 220/1/50	
, District to the second	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
MH-2200-5600	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 5600 x 2200 x 500 mm connection : 0,36 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	
МН-2200-5800	exhaust hood (centre type) in 4 parts Isselbaecher	
	Dimensions : 5800 x 2200 x 500 mm connection : 0,36 kW - 220/1/50	
	hood housing with ambient grease-collecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system	
	execution : stainless steel	

exhaust hood Isselbaecher kitchen equipment GmbH

MH-2200-6000



exhaust hood (centre type) in 4 parts Isselbaecher

Dimensions : 6000 x 2200 x 500 mm connection : 0,36 kW - 220/1/50

hood housing with ambient greasecollecting channel and drain cock incl. lighting, grease filter plates and suspension for connection to (at site) exhaust system

execution : stainless steel