


SPA/EB-1



food distribution trolley
Isselbaecher
SPA/EB-1

Dimensions : 678 x 606 x 900 mm
connection : 0,7 kW - 230/1/50

for 1 x GN 1/1 - 200 mm deep,

1 single basin with drain cock
heating controllable 30 - 90 °C,
all sides heat insulated,

4 swivel casters 125 mm diam.
of which 2 with brakes

execution : stainless steel

SPA/EB-2



food distribution trolley
Isselbaecher
SPA/EB-2

Dimensions : 678 x 916 x 900 mm
connection : 1,4 kW - 230/1/50

for 2 x GN 1/1 - 200 mm deep,

2 single basin with drain cocks
heating controllable 30 - 90 °C,
all sides heat insulated,

4 swivel casters 125 mm diam.
of which 2 with brakes

execution : stainless steel

SPA/EB-2 LS



food distribution trolley
Isselbaecher
SPA/EB-2 LS

Dimensions : 878 x 678 x 900 mm
connection : 1,4 kW - 230/1/50

for 2 x GN 1/1 - 200 mm deep,
2 single basin with drain cocks
heating controllable 30 - 90 °C,
control elements alongside
all sides heat insulated,

4 swivel casters 125 mm diam.
of which 2 with brakes

execution : stainless steel

SPA/EB-3



food distribution trolley
Isselbaecher
SPA/EB-3

Dimensions : 678 x 1256 x 900 mm
connection : 2,1 kW - 230/1/50

for 3 x GN 1/1 - 200 mm deep,

3 single basin with drain cocks
heating controllable 30 - 90 °C,
all sides heat insulated,

4 swivel casters 125 mm diam.
of which 2 with brakes

execution : stainless steel

SPA/EB-3 LS



food distribution trolley
Isselbaecher
SPA/EB-3 LS

Dimensions : 1219 x 678 x 900 mm
connection : 2,1 kW - 230/1/50


for 3 x GN 1/1 - 200 mm deep,
3 single basins with
drain cocks, heating controllable 30 -
90 °C,
control elements alongside

all sides heat insulated,

4 swivel casters 125 mm diam.
of which 2 with brakes

execution : stainless steel

SPA/EB-4



food distribution trolley
Isselbaecher
SPA/EB-4

Dimensions : 678 x 1595 x 900 mm
connection : 2,8 kW - 230/1/50

for 4 x GN 1/1 - 200 mm deep,

4 single basin with drain cocks
heating controllable 30 - 90 °C,
all sides heat insulated,

4 swivel casters 125 mm diam.
of which 2 with brakes

execution : stainless steel

SAW 1



food distribution trolley
Isselbaecher
SAW 1

Dimensions : 750 x 508 x 933 mm
connection : 0,7 kW - 230/1/50

for 1 x GN 1/1 - 200 mm deep,

control element an small side

- 1 basin with drain cock
- heating controllable
- heat insulation
- 4 swivel casters diam. 125 mm, of which
2 with brakes

execution : stainless steel

SAW 2



food distribution trolley
Isselbaecher
SAW 2

Dimensions : 936 x 714 x 933 mm
connection : 1,4 kW - 230/1/50

for 2 x GN 1/1 - 200 mm deep,

control element an small side

- 2 single basins with drain cock,
- heating controllable
- heat insulation
- 4 swivel casters diam. 125 mm, of which
2 with brakes

execution : stainless steel

SAW L-2



food distribution trolley
Isselbaecher
SAW L-2

Dimensions : 900 x 749 x 933 mm
connection : 1,4 kW - 230/1/50

for 2 x GN 1/1 - 200 mm deep,

control element at long side

- 2 single basins with drain cock,
- heating controllable
- heat insulation
- 4 swivel casters diam. 125 mm, of which 2 with brakes

execution : stainless steel

SAW 3



food distribution trolley
Isselbaecher
SAW 3

Dimensions : 1276 x 714 x 933 mm
connection : 2,1 kW - 230/1/50

for 3 x GN 1/1 - 200 mm deep,

control element an small side

- 3 single basins with drain cock
- heating controllable
- heat insulation
- 4 swivel casters, 2 with brakes

execution : stainless steel

SAW L-3



food distribution trolley
Isselbaecher
SAW L-3

Dimensions : 1241 x 749 x 933 mm
connection : 2 kW - 230/1/50


for 3 x GN 1/1 - 200 mm deep,

control element at long side

- 3 single basins with drain cock
- heating controllable
- heat insulation
- 4 swivel casters diam. 125 mm, of which 2 with brakes

execution : stainless steel

SAW 4



food distribution trolley
Isselbaecher
SAW 4

Dimensions : 1615 x 714 x 933 mm
connection : 2,8 kW - 230/1/50


for 4 x GN 1/1 - 200 mm deep,

control element an small side

- 4 basins with drain cock,
- heating controllable
- heat insulation
- 4 swivel casters diam. 125 mm, of which 2 with brakes

execution : stainless steel

SAW L-4



food distribution trolley
Isselbaecher
SAW L-4

Dimensions : 1574 x 749 x 933 mm
connection : 2,8 kW - 230/1/50

for 4 x GN 1/1 - 200 mm deep,

control element at long side

- 4 basins with drain cock,
- heating controllable
- heat insulation
- 4 swivel casters diam. 125 mm, of which 2 with brakes

	execution : stainless steel
<p>SAG 2</p> 	<p>food distribution trolley Isselbaecher SAG 2</p> <p>Dimensions : 936 x 714 x 933 mm connection : 1,9 kW - 230/1/50</p> <p>for 2 x GN 1/1 - 200 mm deep,</p> <ul style="list-style-type: none"> - 2 single basins with drain cock, - heating controllable - heat insulation - 2 cupboards with ea. 6 pairs of support ledges, - separately heatable and controllable cupboard - 4 swivel casters diam. 125 mm, 2 with brakes <p>execution : stainless steel</p>
<p>SAG 2 S/G</p> 	<p>sliding lid with galery Isselbaecher SAG 2 S/G</p> <ul style="list-style-type: none"> - rail on all sides, 50 mm high - plastic rails <p>- execution : stainless steel</p>
<p>SAG 3</p> 	<p>food distribution trolley Isselbaecher SAG 3</p> <p>Dimensions : 1276 x 714 x 933 mm connection : 2,85 kW - 230/1/50</p> <p>for 3 x GN 1/1 - 200 mm deep,</p> <ul style="list-style-type: none"> - 3 single basins with drain cock - heating controllable - heat insulation - 3 cupboards with ea. 6 pairs of support ledges, - separately heatable and controllable cupboard - 4 swivel casters diam. 125 mm, 2 with brakes <p>execution : stainless steel</p>
<p>SAG 3 S/G</p> 	<p>sliding lid with galery Isselbaecher SAG 3 S/G</p> <ul style="list-style-type: none"> - rail on all sides, 50 mm high - plastic rails <p>- execution : stainless steel</p>