


	convection ovens
BPG 054 M 	gas-circulated air oven/bakery model Isselbaecher BPG 054 M Dimensions : 920 x 695 x 630 mm Anschlusswert: Gas 8,5 kW Elt. 0,25 kW - 230/1/50 to take: 5 baking trays 600 x 400 mm - mit Beschwädung, - 1 glass door, double glazed - mechanically, manual operation accessories : 2 baking sheets aluminium 600 x 400 x 20 mm execution : stainless steel
ASR 04 	base frame ASR 04 Dimensions : 884 x 555 x 910 mm execution : stainless steel
ASP 04 	base frame ASP 04 Dimensions : 884 x 555 x 910 mm - with built-in support rails - capacity: 5 trays 600 x 400 mm execution : stainless steel
AAU 04 	proofing cabinet AAU 04 Dimensions : 920 x 555 x 910 mm connection : 2,6 kW - 230/1/50 - electro mechanical control - swatch production execution : stainless steel
LD 25 	hand shower LD 25 - complete with hose made of stainless steel stainless, connections and connections (2,5 m)

BPG 074 M



gas-circulated air oven/bakery model
 Isselbaecher
 BPG 074 M

Dimensions : 950 x 805 x 790 mm
 Anschlusswert: Gas 10 kW
 Elt. 0,5 kW - 230/1/50

to take:
 7 baking trays 600 x 400 mm

- mit Beschwadung,
- zwei Lueftergeschwindigkeiten
- 1 glass door, double glazed
- mechanically, manual operation

accessories : 2 baking sheets aluminium
 600 x 400 x 20 mm

execution : stainless steel

BPG 104 M



gas-circulated air oven/bakery model
 Isselbaecher
 BPG 104 M

Dimensions : 950 x 850 x 1010 mm
 connection : gas 18 kW
 electric 1 kW - 230/1/50


to take:
 10 baking trays 600 x 400 mm

- mit Beschwadung,
- zwei Lueftergeschwindigkeiten
- 1 glass door, double glazed
- mechanically, manual operation

accessories : 2 baking sheets aluminium
 600 x 400 x 20 mm

execution : stainless steel

A04 PES



convection oven/bakery model
 Isselbaecher
 A04 PES

Dimensions : 875 x 705 x 590 mm
 connection : 6,25 kW - 400/3/50

to take:
 4 baking trays 600 x 400 mm
 (clearance 95 mm)

with lights
 1 glass door

execution : stainless steel

A05 PES M



electric convection oven/bakery model
 Isselbaecher
 A05 PES M

Dimensions : 875 x 705 x 590 mm
 connection : 6,25 kW - 400/3/50

to take:
 5 baking trays 600 x 400 mm
 (clearance 75 mm)

with lights
 1 glass door


execution : stainless steel

convection ovens



A08 PES M 	electric convection oven/bakery model Isselbaecher A08 PES Dimensions : 875 x 705 x 970 mm connection : 12.5 kW - 400/3/50 to take: 8 baking trays 600 x 400 mm (clearance 95 mm) with lights 1 glass door execution : stainless steel
A10 PES M 	convection oven/bakery model Isselbaecher A10 PES M Dimensions : 875 x 705 x 970 mm connection : 12.5 kW - 400/3/50 to take: 10 baking trays 600 x 400 mm (clearance 75 mm) with lights 1 glass door execution : stainless steel
BPE 054 M 	electric convection oven/bakery model Isselbaecher BPE 054 M Dimensions : 920 x 695 x 630 mm connection : 6,25 kW - 400/3/50 to take: 5 baking trays 600 x 400 mm - steaming, - interior light - 1 glass door, double glazed - mechanically, manual operation accessories : 2 baking sheets aluminium 600 x 400 x 20 mm execution : stainless steel
BPE 074 M 	electric convection oven/bakery model Isselbaecher BPE 074 M Dimensions : 950 x 805 x 790 mm connection : 8 kW - 400/3/50 to take: 7 baking trays 600 x 400 mm - steaming, - interior light - 2 fan speeds - 1 glass door, double glazed - mechanically, manual operation accessories : 2 baking sheets aluminium 600 x 400 x 20 mm execution : stainless steel
BPE 104 M 	electric convection oven/bakery model Isselbaecher BPE 104 M Dimensions : 950 x 850 x 1010 mm connection : 16 kW - 400/3/50 to take: 10 baking trays 600 x 400 mm - steaming, - interior light - 2 fan speeds - 1 glass door, double glazed

convection ovens


Isselbaecher
kitchen equipment GmbH

	- mechanically, manual operation accessories : 2 baking sheets aluminium 600 x 400 x 20 mm execution : stainless steel
K-5H/00 Basic/KC 00 	convection oven/bakery model Isselbaecher K-5H/00 Basic/KC 00 Dimensions : 780 x 855 x 695 mm connection : 6,0 kW - 400/3/50 - to take 5 baking sheets 600 x 400 mm - distance of rails : 80 mm - c/w lid - 1 door, ginged at left side - thermostate - mechanical timer - push button for water injection - main switch - control lamp for temperature execution : stainless steel
KE-20+H/00 	proofing cabinet Isselbaecher KE-20+H/00 Dimensions : 780 x 885 x 966 mm - for 20 baking sheets 600 x 400 mm - distance between rails 60 mm - window - humidity controller - thermostatically controllable - mobile on 4 swivel casters 2 with brakes execution : stainless steel
K-5+H/00 KS 90/KC 00 	convection oven/bakery model Isselbaecher K-5+H/00 KS 90/KC 00 Dimensions : 780 x 855 x 695 mm connection : 6,0 kW - 400/3/50 - to take 5 baking sheets 600 x 400 mm - distance of rails : 80 mm - c/w lid - 1 door, ginged at left side - following parameter programmable : baking temperature baking time beginning of water injection - up to 8 different program sequences programmable execution : stainless steel
KX-9+H 	convection oven/bakery model Isselbaecher KX-9+H Dimensions : 840 x 920 x 1070 mm connection : 14,5 kW - 400/3/50 to take: 9 baking sheets 600x400 mm 1 door hinged left side with water injection, execution: bakery execution : stainless steel
KXC 	exhaust hood KXC Dimensions : 840 x 1020 x 160 mm to be connected to (at site) exhaust system execution : stainless steel


convection ovens

KXE-20+h 	proofing cabinet KXE-20+h connection : 1,2 kW - 230/1/50 to take 20 baking sheets 600x400 mm thermostatical control with humidifier movable with 4 swivel casters, of which 2 lockable execution : stainless steel
KXS-10 	base frame KXS-10 to take 10 baking sheets 600x400 mm execution : stainless steel
KX-10+H0060x40KS90/K 	convection oven/bakery model Isselbaecher KX-10+H/0060x40KS90/KXC00 Dimensions : 838 x 945 x 1070 mm Anschlusswert : 14,5 kW - 400/3/50 - to take 10 baking sheets 600 x 400 mm - distance of rails : 93 mm - c/w lid - 1 door, ginged at left side - following parameter programmable : baking temperature baking time beginning of water injection - up to 8 different program sequences programmable execution : stainless steel
GU 3.0403 	convection oven/bakery model Isselbaecher GU 3.0403 Dimensions : 600 x 720 x 510 mm connection : 3,4 kW - 230/1/50 - to take : - for 3 baking sheets 445 x 350 mm - distance of rails : 80 mm - 1 door, hinged at right side - analog control - with water tank, selectively with water connection execution : stainless steel
Gu-Zwischenfach 	intermediate compartment GU-Z - height : 360 mm - with 4 pairs of rails - cladding right/left side
Gu-Gaerschrank/Fuss 	proofing cabinet on legs GU-Gaer Dimensions : 600 x 630 x 850 mm - capacity : 6 baking sheets



convection ovens

Gu-Unterg. 1000/10 	base frame GU-1000/10 Dimensions : x x 1000 mm - for 10 baking sheets
EC 6.0604 	convection oven/bakery model Isselbaecher EC 6.0604 Dimensions : 900 x 850 x 780 mm connection : 9,3 kW - 40073/50 - to take : - 6 baking sheets 600 x 400 mm - 1 door, hinged at right side - with steam injection execution : stainless steel
EC-Gaer AS/773 	proofing cabinet EC/773 Anschlusswert : 2,2 kW - 230/1/50 - height : 773 mm - for 2 x 8 baking sheets - analog control - evaporator - glass doors
EC-UST-930/18 	base frame EC-UST/930-18 - height : 930 mm - with rails for 2 x 9 baking sheets
EC-Z-560/6 	intermediate compartment 560 - height : 560 mm - for 6 baking sheets
EC 10.0604 	convection oven/bakery model Isselbaecher EC 10.0604 Dimensions : 900 x 850 x 1095 mm connection : 16,0 kW - 400/3/50 - to take : - 10 baking sheets 600 x 400 mm - with programmable control - 1 door, hinged at right side - with steam injection execution : stainless steel




convection ovens

EC-Gaer AS/773 	proofing cabinet EC/773 Anschlusswert : 2,2 kW - 230/1/50 - height : 773 mm - for 2 x 8 baking sheets - analog control - evaporator - glass doors
EC-UST-610/12 	base frame EC-UST/610-12 - height : 610 mm - with rails for 2 x 6 baking sheets
EC-Z-320/8 	intermediate compartment 320-2x4 - height : 320 mm - for 2 x 4 baking sheets
AE 4.0604 	convection oven/bakery model Isselbaecher AE 4.0604 Dimensions : 900 x 850 x 710 mm connection : 2,2 kW - 230/1/50 - to take 4 baking sheets 600 x 400 mm - electronic program control - with steam injection - 1 door, hinged at right side - el. water counter execution : stainless steel
AE-Gaer AS/773 	proofing cabinet AS/773 Anschlusswert : 2,2 kW - 230/1/50 - height : 773 mm - for 2 x 8 baking sheets - analog control - evaporator - glass doors
AE-Gaer FP/773 	proofing cabinet FP/773 Anschlusswert : 2,2 kW - 230/1/50 - height : 773 mm - for 2 x 8 baking sheets - programmable control - proofing convector - glass doors



convection ovens

AE-UST-930/18 	base frame UST/930-18 - height : 930 mm - with rails for 2 x 9 baking sheets
AE-Z-320/8 	intermediate compartment 320-2x4 - height : 320 mm - for 2 x 4 baking sheets
AE 6.0604 	convection oven/bakery model Isselbaecher AE 6.0604 Dimensions : 900 x 850 x 870 mm connection : 11,3 kW - 400/3/50 - to take 6 baking sheets 600 x 400 mm - electronic program control - with steam injection - 1 door, hinged at right side - el. water counter execution : stainless steel
AE-Gaer AS/773 	proofing cabinet AS/773 Anschlusswert : 2,2 kW - 230/1/50 - height : 773 mm - for 2 x 8 baking sheets - analog control - evaporator - glass doors
AE-Gaer FP/773 	proofing cabinet FP/773 Anschlusswert : 2,2 kW - 230/1/50 - height : 773 mm - for 2 x 8 baking sheets - programmable control - proofing convector - glass doors
AE-UST-770/16 	base frame UST/770-16 - height : 770 mm - with rails for 2 x 8 baking sheets

convection ovens

AE-Z-320/8 	intermediate compartment 320-2x4 - height : 320 mm - for 2 x 4 baking sheets
AE 8.0604 	convection oven/bakery model Isselbaecher AE 8.0604 Dimensions : 900 x 850 x 1030 mm connection : 15,4 kW - 400/3/50 - to take 8 baking sheets 600 x 400 mm, - electronic program control - with steam injection - 1 door, hinged at right side - el. water counter execution : stainless steel
AE-Gaer AS/613-12 	proofing cabinet AS/613-12 Anschlusswert : 2,2 kW - 230/1/50 - height : 613 mm - for 2 x 6 baking sheets - analog control - evaporator - glass doors
AE-Gaer FP/773 	proofing cabinet FP/773 Anschlusswert : 2,2 kW - 230/1/50 - height : 773 mm - for 2 x 8 baking sheets - programmable control - proofing convector - glass doors
AE-UST-610/12 	base frame UST/610-12 - height : 610 mm - with rails for 2 x 6 baking sheets
AE-Z-320/6 	intermediate compartment 320-2x3 - height : 320 mm - for 2 x 3 baking sheets

convection ovens

AE 10.0604 	convection oven/bakery model Isselbaecher AE 10.0604 Dimensions : 900 x 850 x 1190 mm connection : 19,7 kW - 400/3/50 - to take 10 baking sheets 600x400 mm - electronic program control - with steam injection - 1 door, hinged at right side - el. water counter execution : stainless steel
AE-Gaer AS/613-12 	proofing cabinet AS/613-12 Anschlusswert : 2,2 kW - 230/1/50 - height : 613 mm - for 2 x 6 baking sheets - analog control - evaporator - glass doors
AE-Gaer FP/773 	proofing cabinet FP/773 Anschlusswert : 2,2 kW - 230/1/50 - height : 773 mm - for 2 x 8 baking sheets - programmable control - proofing convector - glass doors
AE-UST-610/12 	base frame UST/610-12 - height : 610 mm - with rails for 2 x 6 baking sheets
AE-Z-320/8 	intermediate compartment 320-2x4 - height : 320 mm - for 2 x 4 baking sheets