

Hot display case

Isselbaecher
kitchen equipment GmbH

WD 100 	heated show case Isselbaecher WD 100 Dimensions : 590 x 350 x 285 mm connection : 0,65 KW-230/1/50 with 1 shelf and humidity control execution : stainless steel
WDL 100 	heated show case Isselbaecher WDL 100 Dimensions : 590 x 350 x 375 mm connection : 0,65 KW-230/1/50 with 1 shelf incl. lighting and humidity control execution : stainless steel
WD 200 	heated show case Isselbaecher WD 200 Dimensions : 590 x 350 x 390 mm connection : 0,65 KW-230/1/50 with 2 shelves and humidity control execution : stainless steel
WDL 200 	heated show case Isselbaecher WDL 200 Dimensions : 590 x 350 x 480 mm connection : 0,65 KW-230/1/50 with 2 shelves incl. lighting and humidity control execution : stainless steel
ECV1050 	Hot display case Isselbaecher ECV 1050 Dimensions : 550 x 770 x 550 mm connection : 1,5 KW - 230/1/50 temp.-range: 30°C - 110°C - with intermediate deposit and lighting - interior climatization by means of hot air and humidifying container - to take 1 x GN 1/1 execution : stainless steel
ECV2076 	Hot display case Isselbaecher ECV 2076 Dimensions : 755 x 770 x 550 mm connection : 1,9 kW - 230/1/50 temp.-range: 30°C - 110°C - with intermediate deposit and lighting - interior climatization by means of hot air and humidifying container - to take 2 x GN 1/1 execution : stainless steel

ECV3110



Hot display case
Isselbaecher
ECV 3110

Dimensions : 1092 x 770 x 550 mm
connection : 3,3 kW - 230/1/50

temp.-range: 30°C - 110°C
- with intermediate deposit and lighting
- interior climatisation by means of hot air
and humidifying container
- for storing 3 x GN 1/1

execution : stainless steel

ECV4143



Hot display case
Isselbaecher
ECV 4143

Dimensions : 1430 x 770 x 550 mm
connection : 3,3 kW - 230/1/50

temp.-range: 30°C - 110°C
- with intermediate deposit and lighting
- interior climatisation by means of hot air
and humidifying container
- to take 4 x GN 1/1

execution : stainless steel