

94/04PEI110



electric fast boiling kettle  
 Isselbaecher  
 94/04PEI110

Dimensions : 800 x 900 x 900 mm  
 connection : 16,0 kW - 400/3/50

- round kettle
- content : 110 ltrs.
- with indirect heating
- drain tap 2"

execution : stainless steel

94/04PEI150




electric fast boiling kettle  
 Isselbaecher  
 94/04PEI150

Dimensions : 800 x 900 x 900 mm  
 connection : 18,0 kW - 400/3/50

- round kettle
- content : 150 ltrs.
- with indirect heating
- drain tap 2"

execution : stainless steel

OLPM 1 IE 200




electric fast boiling kettle  
 Isselbaecher  
 OLPM 1 IE 200

Dimensions : 1000 x 1150 x 900 mm  
 connection : 24 kW - 400/3/50

round kettle  
 content : 200 litres  
 indirectly heated  
 drain tap 2"

execution : stainless steel

OLPM 1 IE 300



electric fast boiling kettle  
 Isselbaecher  
 OLPM 1 IE 300

Dimensions : 1150 x 1300 x 900 mm  
 connection : 36 kW - 400/3/50

round kettle  
 content : 300 ltrs.  
 indirectly heated  
 drain tap 2"

execution : stainless steel