








gas fast boiling kettle

<p>94/04PGD110</p> 	<p>gas fast boiling kettle Isselbaecher 94/04PGD110</p> <p>Dimensions : 800 x 900 x 900 mm connection : gas 21,0 kW</p> <ul style="list-style-type: none"> - round kettle - content : 115 ltrs. - with direct heating - drain tap 2" - piezo ignition <p>execution : stainless steel</p>
<p>94/04PGD150</p> 	<p>gas fast boiling kettle Isselbaecher 94/04PGD150</p> <p>Dimensions : 800 x 900 x 900 mm connection : gas 21,0 kW</p> <ul style="list-style-type: none"> - round kettle - content : 150 ltrs. - with direct heating - drain tap 2" - piezo ignition <p>execution : stainless steel</p>
<p>94/04PGI110</p> 	<p>gas fast boiling kettle Isselbaecher 94/04PGI110</p> <p>Dimensions : 800 x 900 x 900 mm connection : gas 21,0 kW</p> <ul style="list-style-type: none"> - round kettle - content : 110 ltrs. - with indirect heating - drain tap 2" - piezo ignition <p>execution : stainless steel</p>
<p>94/04PGI150</p> 	<p>gas fast boiling kettle Isselbaecher 94/04PGI150</p> <p>Dimensions : 800 x 900 x 900 mm connection : gas 21,0 kW</p> <ul style="list-style-type: none"> - round kettle - content : 150 ltrs. - with indirect heating - drain tap 2" - piezo ignition <p>execution : stainless steel</p>
<p>OLPM 9 DG 200</p> 	<p>gas fast boiling kettle Isselbaecher OLPM 9 DG 200</p> <p>Dimensions : 900 x 900 x 900 mm connection : gas 28 kW</p> <p>round kettle content : 200 litres directly heated drain tap 2"</p> <p>execution : stainless steel</p>
<p>OLPM 1 DG 300</p> 	<p>gas fast boiling kettle Isselbaecher OPLPM 1 DG 300</p> <p>Dimensions : 1150 x 1130 x 900 mm connection : gas 48 kW</p> <p>round kettle content : 300 ltrs. directly heated drain tap 2"</p> <p>execution : stainless steel</p>

gas fast boiling kettle

OLPM 1 IG 200




gas fast boiling kettle
Isselbaecher
OLPM 1 IG 200

Dimensions : 1000 x 1150 x 900 mm
connection : gas 40 kW

round kettle
content : 200 litres
indirectly heated
drain tap 2"

execution : stainless steel

OLPM 1 IG 300



gas fast boiling kettle
Isselbaecher
OPLPM 1 IG 300

Dimensions : 1150 x 1300 x 900 mm
connection : gas 48 kW

round kettle
content : 300 ltrs.
indirectly heated
drain tap 2"

execution : stainless steel