








	rack conveyor dishwasher
OLAX 161 Compact 	automatic rack type dishwasher, single tank Isselbaecher OLAX 161 Dimensions : 1080 x 720 x 2010 mm connection : 23 kW - 400/3/50-60 rack conveyor machine capacity : 100 racks/hr. 1800 plates/hr. - 1 wash zone, pump 1,75 kW; 500 ltrs./hr. - 1 passage heater 92 kW - foil keys - pressure reducer - for connection to warm water accessories : 1 cutlery basket C47 2 plate racks C40 1 glass rack C44 execution : stainless steel
OLAX 220E (dx) 	automatic rack type dishwasher, single tank Isselbaecher OLAX 220E (dx) Dimensions : 1800 x 750 x 2200 mm connection : 23 kW - 400/3/50-60 direction of basket transport : right to left rack conveyor machine (supply right hand side) capacity : step 1 : 80 racks/hr. 1440 plates/hr. step 2 : 110 racks/hr. 1980 plates/hr. 1 wash zone pump capacity : 2,0 kW/650 ltrs./min. tank capacity : 110 ltrs. tank heating 12 kW 1 freshwater-clear rinse zone pump capacity : 0,1 kW water consumption : 245 ltrs./hr. 2 passage heaters 12 kW ea. - for cold water connection 10°C - automatic tank filling - tank covering strainer system stainless steel accessories : 1 cutlery basket C47 2 plate racks C40 1 universal rack C41 execution : stainless steel
OLAX 220E (sx) 	automatic rack type dishwasher, single tank Isselbaecher OLAX 220E (dx) Dimensions : 1800 x 750 x 2200 mm connection : 23 kW - 400/3/50-60 direction of basket transport : reft to right rack conveyor machine capacity : step 1 : 80 racks/hr. 1440 plates/hr. step 2 : 110 racks/hr. 1980 plates/hr. 1 wash zone pump capacity : 2,0 kW/650 ltrs./min. tank capacity : 110 ltrs. tank heating 12 kW 1 freshwater-clear rinse zone

	pump capacity : 0,1 kW water consumption : 245 ltrs./hr. 2 passage heaters 12 kW ea. - for cold water connection 10°C - automatic tank filling - tank covering strainer system stainless steel accessories : 1 cutlery basket C47 2 plate racks C40 1 universal rack C41 execution : stainless steel
OLAX 250E (sx) 	automatic rack type dishwasher, single tank Isselbaecher OLAX 250E (sx) Dimensions : 2000 x 750 x 1770 mm connection : 32,4 kW - 400/3/50-60 direction of basket transport : left to right rack conveyor machine (supply right hand side) capacity : step 1 : 111 racks/h 1998 plates/hr. 3996 glasses/hr. step 2 : 143 racks/hr. 2574 plates/hr. 5148 glasses/hr. 1 wash zone pump capacity : 2,0 kW/650 ltrs./min. tank capacity : 110 ltrs. tank heating 12 kW 1 freshwater-clear rinse zone pump capacity : 0,1 kW water consumption : 325 ltrs./hr. 2 passage heaters 12 kW ea. - for cold water connection 10°C - automatic tank filling - tank covering strainer system stainless steel accessories : 1 cutlery basket C47 2 plate racks C40 1 universal rack C41 execution : stainless steel
OLAX 250E (dx) 	automatic rack type dishwasher, single tank Isselbaecher OLAX 250E (dx) Dimensions : 2000 x 750 x 1770 mm connection : 32,4 kW - 400/3/50-60 direction of basket transport : right to left rack conveyor machine (supply right hand side) capacity : step 1 : 111 racks/h 1998 plates/hr. 3996 glasses/hr. step 2 : 143 racks/hr. 2574 plates/hr. 5148 glasses/hr. 1 wash zone pump capacity : 2,0 kW/650 ltrs./min. tank capacity : 110 ltrs. tank heating 12 kW 1 freshwater-clear rinse zone pump capacity : 0,1 kW water consumption : 325 ltrs./hr. 2 passage heaters 12 kW ea. - for cold water connection 10°C - automatic tank filling - tank covering strainer system stainless steel accessories : 1 cutlery basket C47

	2 plate racks C40 1 universal rack C41 execution : stainless steel
OLAX 300E (dx) 	automatic rack type dishwasher, double tank Isselbaecher OLAX 300E (dx) Dimensions : 2400 x 750 x 1770 mm connection : 36,2 kW - 400/3/50 direction of basket transport : right to left rack conveyor machine capacity : step 1 : 111 racks/h 1998 plates/hr. 3996 glasses/hr. step 2 : 143 racks/hr. 2574 plates/hr. 5148 plates/hr. 1 pre-washing zone pump capacity : 1,1 kW/550 ltrs./min. tank capacity : 70 ltrs. 1 wash zone pump capacity : 2,0 kW/650 ltrs./min. tank capacity : 110 ltrs. tank heating 12 kW 1 freshwater-clear rinse zone pump capacity : 0,1 kW water consumption : 325 ltrs./hr. 2 passage heaters 12 kW ea. - for cold water connection 10°C - automatic tank filling - tank covering strainer system accessories : 1 cutlery basket C47 2 plate racks C40 1 universal rack C41 execution : stainless steel
OLAX 300E (sx) 	automatic rack type dishwasher, double tank Isselbaecher OLAX 300E (sx) Dimensions : 2400 x 750 x 1770 mm connection : 36,2 kW - 400/3/50 direction of basket transport : left to right rack conveyor machine capacity : step 1 : 111 racks/h 1998 plates/hr. 3996 glasses/hr. step 2 : 143 racks/hr. 2574 plates/hr. 5148 plates/hr. 1 pre-washing zone pump capacity : 1,1 kW/550 ltrs./min. tank capacity : 70 ltrs. 1 wash zone pump capacity : 2,0 kW/650 ltrs./min. tank capacity : 110 ltrs. tank heating 12 kW 1 freshwater-clear rinse zone pump capacity : 0,1 kW water consumption : 325 ltrs./hr. 2 passage heaters 12 kW ea. - for cold water connection 10°C - automatic tank filling - tank covering strainer system accessories : 1 cutlery basket C47 2 plate racks C40 1 universal rack C41 execution : stainless steel

CSA Mono Export 	automatic rack type dishwasher, single tank Isselbaecher CSA Mono Dimensions : 1350 x 785 x 1460 mm connection : approx. 35 kW - 400/3/50 rack conveyor machine capacity : 90 racks/hr. 1650 plates/hr. 240 glasses/hr. 1 wash zone pump capacity : 1,5 kW/1020 ltrs./min. tank capacity : 100 ltrs. tank heating 12 kW 1 freshwater-clear rinse zone water consumption : 260 ltrs./hr. 1 passage heater 21 kW - automatic tank filling - tank covering sieve system s/s - mono rinse execution : stainless steel
CSA Dual Export 	automatic rack type dishwasher, single tank Isselbaecher CSA Dual Dimensions : 1350 x 785 x 1460 mm connection : approx. 35 kW - 400/3/50 rack conveyor machine capacity : 90 racks/hr. 1650 plates/hr. 240 glasses/hr. 1 wash zone pump capacity : 1,5 kW/1020 ltrs./min. tank capacity : 100 ltrs. tank heating 12 kW 1 freshwater-clear rinse zone water consumption : 260 ltrs./hr. 1 passage heater 21 kW - automatic tank filling - tank covering sieve system s/s - dual rinse execution : stainless steel
CSA-E Mono Export 	automatic rack type dishwasher, double tank Isselbaecher CSA-E Mono Dimensions : 1850 x 785 x 1460 mm connection : approx. 35 kW - 400/3/50 rack conveyor machine capacity : 120 racks/hr. 2160 plates/hr. 4320 glasses/hr. 1 pre-wash zone pump capacity : 0,17 kW tank capacity : 30 ltrs. 1 wash zone pump capacity : 1,5 kW/1020 ltrs./min. tank capacity : 100 ltrs. tank heating 12 kW 1 freshwater-clear rinse zone water consumption : 260 ltrs./hr. 1 passage heater 21 kW - automatic tank filling - tank covering sieve system s/s - mono rinse execution : stainless steel

CSA-E Dual Export 	automatic rack type dishwasher, double tank Isselbaecher CSA-E Dual Dimensions : 1850 x 785 x 1460 mm connection : approx. 35 kW - 400/3/50 rack conveyor machine capacity : 140 racks/hr. 2520 plates/hr. 5030 glasses/hr. 1 pre-wash zone pump capacity : 0,17 kW tank capacity : 30 ltrs. 1 wash zone pump capacity : 1,5 kW/1020 ltrs./min. tank capacity : 100 ltrs. tank heating 12 kW 1 freshwater-clear rinse zone water consumption : 260 ltrs./hr. 1 passage heater 21 kW - automatic tank filling - tank covering sieve system s/s - dual rinse execution : stainless steel
CNA Export 	automatic rack type dishwasher, single tank Isselbaecher CNA Dimensions : 1350 x 804 x 1718 mm connection : approx. 41,1 kW - 400/3/50 rack conveyor machine capacity : 120 racks/hr. 2160 plates/hr. 4320 glasses/hr. 1 wash zone pump capacity : 1,5 kW/1200 ltrs./min. tank capacity : 100 ltrs. tank heating 12 kW 1 freshwater-clear rinse zone water consumption : 290 ltrs./hr. 1 flow heater 25 kW - automatic tank filling - autotimer - tank covering sieve system s/s - drain pump - insulated 40 mm - exhaust hood with fan 0,5 kW - built-in main switch - 2 speeds 120/80 sec. execution : stainless steel
CNA-E Export 	automatic rack type dishwasher, double tank Isselbaecher CNA-E Dimensions : 1850 x 792 x 1713 mm connection : approx. 39 kW - 400/3/50 rack conveyor machine capacity : 150 racks/hr. 2700 plates/hr. 5400 glasses /hr. 1 pre-washing zone pump capacity : 0,3 kW/250 ltrs./min. tank capacity : 30 ltrs. 1 wash zone pump capacity : 1,5 kW/1020 ltrs./min. tank capacity : 100 ltrs. tank heating 12 kW 1 freshwater-clear rinse zone water consumption : 290 ltrs./hr. 1 flow heater 25 kW - automatic tank filling - Autotimer - tank covering strainer system - drain pump

	- insulated 40 mm - exhaust hood with fan 0,5 kW execution : stainless steel
CNA-L Export 	automatic rack type dishwasher, double tank Isselbaecher CNA-L Dimensions : 2000 x 783 x 1718 mm connection : approx. 39,55 kW - 40073/50 rack conveyor machine capacity : 180 racks/hr. 3240 plates/hr. 6480 glasses/hr. 1 pre-washing zone pump capacity : 1,1 kW/740 ltrs./min. tank capacity : 54 ltrs. 1 wash zone pump capacity : 1,5 kW/1020 ltrs./min. tank capacity : 100 ltrs. tank heating 12 kW 1 freshwater-clear rinse zone water consumption : 290 ltrs./hr. 1 flow heater 25 kW - automatic tank filling - Autotimer - tank covering strainer system - drain pump - insulated 40 mm - exhaust hood with fan 0,5 kW execution : stainless steel
CNA-S Export 	automatic rack type dishwasher, double tank Isselbaecher CNA-S Dimensions : 2250 x 783 x 1718 mm connection : approx. 39,55 kW - 40073/50 rack conveyor machine 2 speeds 14000 and 18000 rpm. capacity : 150/220 racks/hr. 3960 plates/hr. 7920 glasses/hr. 1 pre-washing zone pump capacity : 1,5 kW/1020 ltrs./min. tank capacity : 100 ltrs. 1 wash zone pump capacity : 1,5 kW/1020 ltrs./min. tank capacity : 100 ltrs. tank heating 12 kW 1 freshwater-clear rinse zone water consumption : 290 ltrs./hr. 1 flow heater 25 kW - automatic tank filling - Autotimer - tank covering strainer system - drain pump - insulated 40 mm - exhaust hood with fan 0,5 kW execution : stainless steel