

electric range

72/02CEPT



electric range
Isselbaecher
72/02CEPT

Dimensions : 400 x 700 x 900 mm
connection : 4,6 kW - 400/3/50

with 2 round hot plates

substructure: open with back wall

execution : stainless steel

74/02CEPT



electric range
Isselbaecher
74/02CEPT

Dimensions : 800 x 700 x 900 mm
connection : 9,2 kW - 400/3/50

with 4 round hot plates

substructure: open with back wall

execution : stainless steel

76/02CEPT



electric range
Isselbaecher
76/02CEPT

Dimensions : 1200 x 700 x 900 mm
connection : 13,8 kW - 400/3/50

with 6 round hot plates

substructure: open with back wall

execution : stainless steel

72/02CEPQ



electric range
Isselbaecher
72/02CEPQ

Dimensions : 400 x 700 x 900 mm
connection : 5,2 kW - 400/3/50

with 2 square hot plates

substructure: open with back wall

execution : stainless steel

74/02CEPQ



electric range
Isselbaecher
74/02CEPQ

Dimensions : 800 x 700 x 900 mm
connection : 10,4 kW - 400/3/50

with 4 square hot plates

substructure: open with back wall

execution : stainless steel

76/02CEPQ



electric range
Isselbaecher
76/02CEPQ

Dimensions : 1200 x 700 x 900 mm
connection : 15,6 kW - 400/3/50

with 6 square hot plates

substructure: open with back wall

execution : stainless steel

electric range

72/02VTCV



electric range
Isselbaecher
72/02VTC

Dimensions : 400 x 700 x 900 mm
connection : 5,0 kW - 400/3/50

glass ceramic-cooking plate
with 2 heating zones

substructure: open with back wall

execution : stainless steel

74/02VTCV



electric range
Isselbaecher
74/02VTCV

Dimensions : 800 x 700 x 900 mm
connection : 10,0 kW - 400/3/50

glass ceramic-cooking plate
with 4 heating zones

substructure: open with back wall

execution : stainless steel

74/02CTE/RUS



electric range
Isselbaecher
74/02CTE/RUS

Dimensions : 800 x 700 x 900 mm
connection : 10,0 kW - 400/3/50

1 large cooking top with 4 heating zones

substructure: open with back wall

execution : stainless steel