


LLP 70 TN



refrigerator
Isselbaecher
LLP 70 TN

Dimensions : 700 x 800 x 1955 mm
connection : 0,31 kw - 230/1/50


content: 700 litres,
GN 2/1
temperature range : +1/+4°C
with thermostatic control,
1 door with handle, lockable,
hinged at right hand side,

cooling machine on top, tropical
for ambient temperature +38°C
forced air cooling, with automatic
defrosting and thaw water evaporation,

accessories : 3 grids GN 2/1
3 pairs of supports

execution: PVC + PET

LLP 140 TN



refrigerator
Isselbaecher
LLP 140 TN

Dimensions : 1400 x 800 x 1955 mm
connection : 0,45 kW - 230/1/50

content: 1400 ltrs.
GN 2/1
temperature range : +0/+10°C
with thermostatic control,
2 doors with handle,
lockable,

cooling machine underneath, tropical execution
execution :
for ambient temperature +38°C
forced air cooling, with automatic
defrosting and thaw water evaporation,

accessories : 6 grids GN 2/1
6 sets of supports

execution: PVC + PET

ARCO 70



refrigerator
Isselbaecher
ARCO 70

Dimensions : 700 x 800 x 2080 mm
connection : 0,24 kW - 230/1/50

content: 700 litres
GN 2/1
temperature range : +0/+10°C
- electronic control,
- 1 door with ergonomic handle

refrigerating machine on top,
forced air cooling, with automatic
defrosting and thaw water evaporation,

accessories : 3 grids GN 2/1
3 pairs of supports

execution : stainless steel

ARCO 70 P



refrigerator
Isselbaecher
ARCO 70 P

Dimensions : 700 x 800 x 2080 mm
connection : 0,24 kW - 230/1/50

content: 700 litres
GN 2/1
- temperature range : 0/+10°C
- electronic control,
- interior lightning
- 1 door with ergonomic handle
- lockable

refrigerating machine on top,

	forced air cooling, with automatic defrosting and thaw water evaporation, accessories : 3 grids GN 2/1 3 pairs of supports execution : stainless steel
ARCO 140 	refrigerator Isselbaecher ARCO 140 Dimensions : 1400 x 800 x 2080 mm connection : 0,48 kW - 230/1/50 content: 1400 ltrs. GN 2/1 temperature range : +0/+10°C - electronic control, - 2 doors with handle, refrigerating machine on top, forced air cooling, with automatic defrosting and thaw water evaporation, accessories : 6 grids GN 2/1 6 sets of supports execution : stainless steel
ARCO 140 P 	refrigerator Isselbaecher ARCO 140 P Dimensions : 1400 x 800 x 2080 mm connection : 0,48 kW - 230/1/50 content: 1400 ltrs. GN 2/1 - temperature range : 0/+10°C - electronic control, - interior lightning - 2 doors with handle, - lockable refrigerating machine on top, forced air cooling, with automatic defrosting and thaw water evaporation, accessories : 6 grids GN 2/1 6 sets of supports execution : stainless steel
KTN 40 	refrigerator Isselbaecher KTN 40 - ALGEO 600 * Dimensions : 600 x 600 x 1870 mm connection : 0,30 kW - 230/1/50 content: 400 ltrs. temperature range : +0/+10°C - electronic control, 1 door with handle, lockable, hinged at right hand side, cooling machine on top, tropical execution for ambient temperature +43°C, forced air cooling, with automatic defrosting and thaw water evaporation, accessories : 3 grids 450 x 470 3 pairs of supports execution : stainless steel

SPA TNN 60



refrigerator
Isselbaecher
SPA TNN 60 - EASY 700 *

Dimensions : 700 x 700 x 2080 mm
connection : 0,3 KW - 230/1/50

content: 600 ltrs.
GN 2/1 reduced - GN 1/1
temperature range : -2/+8°C
- electronic control,
1 door with handle, lockable,
hinged at right hand side,

cooling machine on top, tropical
execution for ambient temperature +43°C,
forced air cooling, with automatic
defrosting and thaw water evaporation,

accessories : 3 grids 550 x 530 mm
3 pairs of supports

execution : stainless steel

SPA TNV 60



refrigerator
Isselbaecher
SPA TNV 60 - EASY 700

Dimensions : 700 x 700 x 2080 mm
connection : 0,3 KW - 230/1/50

content: 600 ltrs.
GN 2/1 reduced - GN 1/1
temperature range : +2/+10°C
- electronic control,
1 glass door with handle
lockable, hinged at right hand side

cooling machine on top, tropical
execution for ambient temperature +43°C,
forced air cooling, with automatic
defrosting and thaw water evaporation,

accessories : 3 grids
3 pairs of supports

execution : stainless steel

SPA TNN 62



refrigerator
Isselbaecher
SPA TNN 62 - EASY 700

Dimensions : 700 x 700 x 2080 mm
connection : 0,3 KW - 230/1/50

content: 600 ltrs.
GN 2/1 reduced - GN 1/1
temperature range : -2/+8°C
- electronic control,
2 half doors with handle,
lockable, hinged at right hand side

cooling machine on top, tropical
execution for ambient temperature +43°C,
forced air cooling, with automatic
defrosting and thaw water evaporation,

accessories : 4 grids
4 set support rails

execution : stainless steel

SPA B 100



refrigerator
Isselbaecher
SPA B 100 - EASY 700

Dimensions : 700 x 700 x 2080 mm
connection : 0,37 kW - 230/1/50

refrigerator for bottle presentation
content: 600 ltrs.
GN 2/1 reduced - GN 1/1
temperature range : +2/+10°C
- electronic control,
- 1 glass door with handle
lockable, hinged at right hand side

	cooling machine on top, tropical execution for ambient temperature +43°C, forced air cooling, with automatic defrosting and thaw water evaporation, accessories : 3 containers on telescopic rails execution : stainless steel
SPA TNN 120 	refrigerator Isselbaecher SPA TNN 120 - EASY 700 * Dimensions : 1400 x 700 x 2080 mm connection : 0,48 kW - 230/1/50 content: 1200 litres GN 2/1 reduced - GN 1/1 temperature range : -2/+8°C - electronic control, 2 doors with handle, lockable, cooling machine on top, tropical execution for ambient temperature +43°C, forced air cooling, with automatic defrosting and thaw water evaporation, accessories : 6 grids 6 sets of supports execution : stainless steel
SPA TNV 120 	refrigerator Isselbaecher SPA TNV 120 - EASY 700 Dimensions : 1400 x 700 x 2080 mm connection : 0,48 kW - 230/1/50 content: 1200 litres GN 2/1 reduced - GN 1/1 temperature range : +2/+10°C - electronic control, 2 glass doors with handles lockable, cooling machine on top, tropical execution for ambient temperature +43°C, forced air cooling, with automatic defrosting and thaw water evaporation, accessories : 6 grids 6 sets of supports execution : stainless steel
SPA TNN 124 	refrigerator Isselbaecher SPA TNN 124 - EASY 700 Dimensions : 1400 x 700 x 2080 mm connection : 0,48 kW - 230/1/50 content: 1200 litres GN 2/1 temperature range : -2/+8°C - electronic control, 4 half doors with handle, lockable, cooling machine on top, tropical execution for ambient temperature +43°C, forced air cooling, with automatic defrosting and thaw water evaporation, accessories : 8 grids GN 2/1 8 sets of supports execution : stainless steel

SPA B 200



refrigerator
Isselbaecher
SPA B 200 - EASY 700

Dimensions : 1400 x 700 x 2080 mm
connection : 0,37 kW - 230/1/50

refrigerator for bottle presentation
content: 1200 litres
GN 2/1 reduced - GN 1/1
temperature range : +2/+10°C
- electronic control,
- 2 glass doors with handle
lockable,

cooling machine on top, tropical
execution for ambient temperature +43°C,
forced air cooling, with automatic
defrosting and thaw water evaporation,

accessories : 6 containers on
telescopic rails

execution : stainless steel

SPA TNN 70



refrigerator
Isselbaecher
SPA TNN 70 - EASY 800

Dimensions : 700 x 800 x 2080 mm
connection : 0,3 KW - 230/1/50

content: 700 litres
GN 2/1
temperature range : -2/+8°C
- electronic control,
1 door with handle, lockable,
hinged at right hand side,

cooling machine on top, tropical
execution for ambient temperature +43°C,
forced air cooling, with automatic
defrosting and thaw water evaporation,

accessories : 3 grids GN 2/1
3 pairs of supports

execution : stainless steel

SPA TN 70



refrigerator
Isselbaecher
SPA TN 70 - EASY 800

Dimensions : 700 x 800 x 2080 mm
connection : 0,3 KW - 230/1/50

content: 700 litres
GN 2/1
temperature range : +1/+4°C
- electronic control,
1 door with handle, lockable,
hinged at right hand side,

cooling machine on top, tropical
execution for ambient temperature +43°C,
forced air cooling, with automatic
defrosting and thaw water evaporation,

accessories : 3 grids GN 2/1
3 pairs of supports

execution : stainless steel

SPA TNN 72



refrigerator
Isselbaecher
SPA TNN 72 - EASY 800

Dimensions : 700 x 800 x 2080 mm
connection : 0,3 KW - 230/1/50

content: 700 litres
GN 2/1
temperature range : -2/+8°C
- electronic control,
2 half doors with handle,
lockable, hinged at right hand side

	cooling machine on top, tropical execution for ambient temperature +43°C, forced air cooling, with automatic defrosting and thaw water evaporation, accessories : 4 grids GN 2/1 4 set support rails execution : stainless steel
SPA TN 72 	refrigerator Isselbaecher SPA TN 72 - EASY 800 Dimensions : 700 x 800 x 2080 mm connection : 0,3 KW - 230/1/50 content: 700 litres GN 2/1 temperature range : +1/+4°C - electronic control, 2 half doors with handle, lockable, hinged at right hand side cooling machine on top, tropical execution for ambient temperature +43°C, forced air cooling, with automatic defrosting and thaw water evaporation, accessories : 4 grids GN 2/1 4 set support rails execution : stainless steel
SPA TNV 70 	refrigerator Isselbaecher SPA TNV 70 - EASY 800 Dimensions : 700 x 800 x 2080 mm connection : 0,3 KW - 230/1/50 content: 700 litres GN 2/1 temperature range : +2/+10°C - electronic control, 1 glass door with handle lockable, hinged at right hand side cooling machine on top, tropical execution for ambient temperature +43°C, forced air cooling, with automatic defrosting and thaw water evaporation, accessories : 3 grids GN 2/1 3 pairs of supports execution : stainless steel
SPA B 120 	refrigerator Isselbaecher SPA B 120 - EASY 800 Dimensions : 700 x 800 x 2080 mm connection : 0,37 kW - 230/1/50 refrigerator for bottle presentation content: 700 litres GN 2/1 temperature range : +2/+10°C - electronic control, - 1 glass door with handle lockable, hinged at right hand side cooling machine on top, tropical execution for ambient temperature +43°C, forced air cooling, with automatic defrosting and thaw water evaporation, accessories : 3 containers on telescopic rails execution : stainless steel

SPA TN 140



refrigerator
Isselbaecher
SPA TN 140 - EASY 800

Dimensions : 1400 x 800 x 2080 mm
connection : 0,48 kW - 230/1/50

content: 1400 ltrs.
GN 2/1
temperature range : +1/+4°C
- electronic control,
2 doors with handle,
lockable,

cooling machine on top, tropical
execution for ambient temperature +43°C,
forced air cooling, with automatic
defrosting and thaw water evaporation,

accessories : 6 grids GN 2/1
6 sets of supports

execution : stainless steel

SPA TNN 140



refrigerator
Isselbaecher
SPA TNN 140 - EASY 800 *

Dimensions : 1400 x 800 x 2080 mm
connection : 0,48 kW - 230/1/50

content: 1400 ltrs.
GN 2/1
temperature range : -2/+8°C
- electronic control,
2 doors with handle,
lockable,

cooling machine on top, tropical
execution for ambient temperature +43°C,
forced air cooling, with automatic
defrosting and thaw water evaporation,

accessories : 6 grids GN 2/1
6 sets of supports

execution : stainless steel

SPA TNV 140



refrigerator
Isselbaecher
SPA TNV 140 - EASY 800

Dimensions : 1400 x 890 x 2080 mm
connection : 0,48 kW - 230/1/50

content: 1400 ltrs.
GN 2/1
temperature range : +2/+10°C
- electronic control,
2 glass doors with handles
lockable,

cooling machine on top, tropical
execution for ambient temperature +43°C,
forced air cooling, with automatic
defrosting and thaw water evaporation,

accessories : 6 grids GN 2/1
6 sets of supports

execution : stainless steel

SPA TNN 144



refrigerator
Isselbaecher
SPA TNN 144 - EASY 800

Dimensions : 1400 x 800 x 2080 mm
connection : 0,48 kW - 230/1/50

content: 1400 ltrs.
GN 2/1
temperature range : -2/+8°C
- electronic control,
4 half doors with handle,
lockable,

cooling machine on top, tropical

	execution for ambient temperature +43°C, forced air cooling, with automatic defrosting and thaw water evaporation, accessories : 8 grids GN 2/1 8 sets of supports execution : stainless steel
SPA B 240 	refrigerator Isselbaecher SPA B 240 - EASY 800 Dimensions : 1400 x 800 x 2080 mm connection : 0,37 kW - 230/1/50 refrigerator for bottle presentation content: 1400 ltrs. GN 2/1 temperature range : +2/+10°C - electronic control, - 2 glass doors with handle lockable, cooling machine on top, tropical execution for ambient temperature +43°C, forced air cooling, with automatic defrosting and thaw water evaporation, accessories : 6 containers on telescopic rails execution : stainless steel
SPA TN 144 	refrigerator Isselbaecher SPA TN 144 - EASY 800 Dimensions : 1400 x 800 x 2080 mm connection : 0,48 kW - 230/1/50 content: 1400 ltrs. GN 2/1 temperature range : +1/+4°C - electronic control, 4 half doors with handle, lockable, cooling machine on top, tropical execution for ambient temperature +43°C, forced air cooling, with automatic defrosting and thaw water evaporation, accessories : 8 grids GN 2/1 8 sets of supports execution : stainless steel
SPAC TNN 35/35 	refrigerator Isselbaecher SPAC TNN 35/35-EASY 800 Dimensions : 700 x 800 x 2080 mm connection : 0,35 KW - 230/1/50 GN 2/1 temperature range : above -2/+8°C (300 ltrs.) below -2/+8°C (300 ltrs.) - electronic control, 2 half doors with handle, lockable, hinged at right hand side cooling machine on top, tropical execution for ambient temperature +43°C, forced air cooling, with automatic defrosting and thaw water evaporation, accessories : 4 grids GN 2/1 4 set support rails execution : stainless steel

SPAC TNN 70/70



refrigerator
 Isselbaecher
 SPAC TNN 70/70 - EASY 800

Dimensions : 1400 x 800 x 2080 mm
 connection . 0,59 kW - 23071/50

GN 2/1
 temperature range :
 recht -2/+8°C (600 ltrs.)
 left -2/+8°C (600 ltrs.)
 - electronic control,
 2 doors with handle,
 lockable,

 cooling machine on top, tropical
 execution for ambient temperature +43°C,
 forced air cooling, with automatic
 defrosting and thaw water evaporation,

accessories : 6 grids GN 2/1
 6 sets of supports

execution : stainless steel

SPAC 35/35



refrigerator/freezer
 Isselbaecher
 SPAC 35/35 - EASY 800

Dimensions : 700 x 800 x 2080 mm
 connestion : 0,53 kW - 230/1/50

GN 1/1
 temperature range :
 above -2/+8°C (300 ltrs.)
 below -18/-21°C (300 ltrs.)
 - electronic control,
 2 half doors with handle,
 lockable, hinged at right hand side

cooling machine on top, tropical
 execution for ambient temperature +43°C,
 forced air cooling, with automatic
 defrosting and thaw water evaporation,

accessories : 4 grids GN 2/1
 4 set support rails

execution : stainless steel

SPAC 70/70



refrigerator/freezer
 Isselbaecher
 SPAC 70/70 - EASY 800

Dimensions : 1400 x 800 x 2080 mm
 connection : 0,8 kW - 230/1/50

GN 1/1
 temperature range :
 above -2/+8°C (600 ltrs.)
 below -18/-21°C (600 ltrs.)
 - electronic control,
 2 doors with handle,
 lockable,

cooling machine on top, tropical
 execution for ambient temperature +43°C,
 forced air cooling, with automatic
 defrosting and thaw water evaporation,

accessories : 6 grids GN 2/1
 6 sets of supports

execution : stainless steel

KSA TN 70



refrigerator
 Isselbaecher
 KSA TN 70 - SUPREME 850 *

Dimensions : 740 x 800 x 2080 mm
 connection : 0,3 KW - 230/1/50

content: 630 litres
 GN 2/1
 temperature range : -2/+8°C
 - electronic control,
 with data-diagnosis
 1 door with handle, lockable,
 hinged at right hand side,

cooling machine on top, tropical
 execution for ambient temperature +43°C,
 forced air cooling, with automatic
 defrosting and thaw water evaporation,

accessories : 3 grids GN 2/1
 3 pairs of supports

execution : stainless steel

KSA TN 72



refrigerator
 Isselbaecher
 KSA TN 72 - SUPREME 850

Dimensions : 740 x 800 x 2080 mm
 connection : 0,3 KW - 230/1/50

content: 630 litres
 GN 2/1
 temperature range : -2/+8°C
 - electronic control,
 with data-diagnosis
 2 half doors with handle,
 lockable, hinged at right hand side

cooling machine on top, tropical
 execution for ambient temperature +43°C,
 forced air cooling, with automatic
 defrosting and thaw water evaporation,

accessories : 4 grids GN 2/1
 4 set support rails

execution : stainless steel

KSA TNV 70



refrigerator
 Isselbaecher
 KSA TNV 70 - SUPREME 850

Dimensions : 740 x 800 x 2080 mm
 connection : 0,3 KW - 230/1/50

content: 630 litres
 GN 2/1
 temperature range : +2/+10°C
 - electronic control,
 with data-diagnosis
 1 glass door with handle
 lockable, hinged at right hand side

cooling machine on top, tropical
 execution for ambient temperature +43°C,
 forced air cooling, with automatic
 defrosting and thaw water evaporation,

accessories : 3 grids GN 2/1
 3 pairs of supports

execution : stainless steel

KSAC 35/35


 refrigerator/freezer
 Isselbaecher
 KSAC 35/35-SUPREME 850

 Dimensions : 740 x 800 x 2080 mm
 connection : 0,48 kW - 230/1/50

 GN 2/1
 temperature range :
 above -2/+8°C (285 ltrs.)
 below -15/-25°C (285 ltrs.)
 - electronic control,
 with data-diagnosis
 2 half doors with handle,
 lockable, hinged at right hand side

 cooling machine on top, tropical
 execution for ambient temperature +43°C,
 forced air cooling, with automatic
 defrosting and thaw water evaporation,

 accessories : 4 grids GN 2/1
 4 set support rails

execution : stainless steel

KSA TN 140


 refrigerator
 Isselbaecher
 KSA TN 140 - SUPREME 850

 Dimensions : 1480 x 800 x 2080 mm
 connection : 0,48 kW - 230/1/50

 content: 1405 ltrs.
 GN 2/1
 temperature range : -2/+8°C
 - electronic control,
 with data-diagnosis
 2 doors with handle,
 lockable,

 cooling machine on top, tropical
 execution for ambient temperature +43°C,
 forced air cooling, with automatic
 defrosting and thaw water evaporation,

 accessories : 6 grids GN 2/1
 6 sets of supports

execution : stainless steel

KSA TN 144


 refrigerator
 Isselbaecher
 KSA TN 144 - SUPREME 850

 Dimensions : 1480 x 800 x 2080 mm
 connection : 0,48 kW - 230/1/50

 content: 1405 ltrs.
 GN 2/1
 temperature range : -2/+8°C
 - electronic control,
 with data-diagnosis
 4 half doors with handle,
 lockable,

 cooling machine on top, tropical
 execution for ambient temperature +43°C,
 forced air cooling, with automatic
 defrosting and thaw water evaporation,

 accessories : 8 grids GN 2/1
 8 sets of supports

execution : stainless steel

KSA TNV 140



refrigerator
 Isselbaecher
 KSA TNV 140 - SUPREME 850

Dimensions : 1480 x 800 x 2080 mm
 connection : 0,48 kW - 230/1/50

content: 1405 ltrs.
 GN 2/1
 temperature range : -2/+8°C
 - electronic control,
 with data-diagnosis
 2 glass doors with handles
 lockable,

cooling machine on top, tropical
 execution for ambient temperature +43°C,
 forced air cooling, with automatic
 defrosting and thaw water evaporation,

accessories : 6 grids GN 2/1
 6 sets of supports

execution : stainless steel

KSAC TN 70/70



refrigerator
 Isselbaecher
 KSAC TN 70/70-SUPREME 850

Dimensions : 1480 x 800 x 2080 mm
 connection : 0,3 KW - 230/1/50

GN 2/1
 temperature range :
 right -2/+8°C (630 ltrs.)
 left -2/+8°C (630 ltrs.)
 - electronic control,
 with data-diagnosis
 2 doors with handle,
 lockable, hinged at right hand side

cooling machine on top, tropical
 execution for ambient temperature +43°C,
 forced air cooling, with automatic
 defrosting and thaw water evaporation,

accessories : 6 grids GN 2/1
 6 sets of supports

execution : stainless steel

KSAC TN 105/35



refrigerator
 Isselbaecher
 KSAC TN 105/35-SUPREME850

Dimensions : 1480 x 800 x 2080 mm
 connection : 0,28 kW - 230/1/50

content: 1265 ltrs. - GN 2/1
 temperature range : -2/+8°C
 - electronic control,
 with data-diagnosis
 1 full door and 2 half doors with
 handle, lockable,

cooling machine on top, tropical
 execution for ambient temperature +43°C,
 forced air cooling, with automatic
 defrosting and thaw water evaporation,

accessories : 7 grids GN 2/1
 7 sets of supports

execution : stainless steel

KSA P 70



fish refrigerator
 Isselbaecher
 KSA P 70 - SUPREME 850

Dimensions : 740 x 800 x 2080 mm
 connection : 0,3 KW - 230/1/50

content: 630 litres
 GN 2/1
 temperature range : -6/+4°C
 - electronic control,
 with data-diagnosis
 1 door with handle, lockable,
 hinged at right hand side,

 cooling machine on top, tropical
 execution for ambient temperature +43°C,
 forced air cooling, with automatic
 defrosting and thaw water evaporation,

accessories : 12 plastic containers GN
 2/1

execution : stainless steel

KSAP TN 35/35



fish refrigerator
 Isselbaecher
 KSAP TN 35/35-SUPREME 850

Dimensions : 740 x 800 x 2080 mm
 connection : 0,23 kW - 230/1/50

GN 2/1
 temperature range :
 above -2/+8°C (285 ltrs.)
 below -6/+4°C (285 ltrs.)
 - electronic control,
 with data-diagnosis
 2 half doors with handle,
 lockable, hinged at right hand side

 cooling machine on top, tropical
 execution for ambient temperature +43°C,
 forced air cooling, with automatic
 defrosting and thaw water evaporation,

accessories : 2 grids GN 2/1
 6 plastic containers GN 2/1

execution : stainless steel

KSA P 140



fish refrigerator
 Isselbaecher
 KSA P 140 - SUPREME 850

Dimensions : 1480 x 800 x 2080 mm
 connection : 0,48 kW - 230/1/50

content: 1405 ltrs.
 GN 2/1
 temperature range : -6/+4°C
 - electronic control,
 with data-diagnosis
 2 doors with handle,
 lockable,

 cooling machine on top, tropical
 execution for ambient temperature +43°C,
 forced air cooling, with automatic
 defrosting and thaw water evaporation,

accessories : 24 plastic containers GN
 1/1

execution : stainless steel

KSAP TN 70/70



fish refrigerator
Isselbaecher
KSAP TN 70/70-SUPREME 850

Dimensions : 1480 x 800 x 2080 mm
connection : 0,3 KW - 230/1/50

GN 2/1
temperature range :
right -2/+8°C (630 ltrs.)
left -6/+4°C (630 ltrs.)
- electronic control,
with data-diagnosis
2 doors with handle,
lockable,

cooling machine on top, tropical
execution for ambient temperature +43°C,
forced air cooling, with automatic
defrosting and thaw water evaporation,

accessories : 3 grids GN 2/1
12 plastic containers GN
1/1

execution : stainless steel

KSAP TN 105/35



fish refrigerator
Isselbaecher
KSAP TN 105/35-SUPREME850

Dimensions : 1480 x 800 x 2080 mm
connection : 0,28 kW - 230/1/50

content: 1265 ltrs. - GN 2/1
temperature range :
-2/+8°C (980)
-6/+4°C (285)
- electronic control,
with data-diagnosis
1 full door and 2 half doors with
handle, lockable,

cooling machine on top, tropical
execution for ambient temperature +43°C,
forced air cooling, with automatic
defrosting and thaw water evaporation,

accessories : 5 grids GN 2/1
6 plastic containers GN 1/1

execution : stainless steel

KSAC 35/35



refrigerator/freezer
Isselbaecher
KSAC 35/35-SUPREME 850

Dimensions : 740 x 800 x 2080 mm
connection : 0,48 kW - 230/1/50

GN 2/1
temperature range :
above -2/+8°C (285 ltrs.)
below -15/-25°C (285 ltrs.)
- electronic control,
with data-diagnosis
2 half doors with handle,
lockable, hinged at right hand side

cooling machine on top, tropical
execution for ambient temperature +43°C,
forced air cooling, with automatic
defrosting and thaw water evaporation,

accessories : 4 grids GN 2/1
4 set support rails

execution : stainless steel

KSAP BT 35/35



refrigerator/freezer - fish
Isselbaecher
KSAP BT 35/35-SUPREME 850

Dimensions : 740 x 800 x 2080 mm
connection : 0,48 kW - 230/1/50

GN 2/1
temperature range :
above -6/+4°C (285 ltrs.)
below -15/-25°C (285 ltrs.)
- electronic control,
with data-diagnosis
2 half doors with handle,
lockable, hinged at right hand side

cooling machine on top, tropical
execution for ambient temperature +43°C,
forced air cooling, with automatic
defrosting and thaw water evaporation,

accessories : 2 grids GN 2/1
6 plastic containers GN 2/1

execution : stainless steel

KSAC 70/70



refrigerator/freezer
Isselbaecher
KSAC 70/70-SUPREME 850

Dimensions : 1480 x 800 x 2080 mm
connection : 0,75 kW - 230/1/50

GN 2/1
temperature range :
right -2/+8°C (630 ltrs.)
left -15/-25°C (630 ltrs.)
- electronic control,
with data-diagnosis
2 doors with handle,
lockable,

cooling machine on top, tropical
execution for ambient temperature +43°C,
forced air cooling, with automatic
defrosting and thaw water evaporation,

accessories : 6 grids GN 2/1
6 sets of supports

execution : stainless steel

KSAC 105/35



refrigerator/freezer
Isselbaecher
KSAC 105/35-SUPREME 850

Dimensions : 1480 x 800 x 2080 mm
connection : 0,75 kW - 230/1/50

content: 1265 ltrs. - GN 2/1
temperature range :
-2/+8°C (350)
-15/-25°C (1050)
- electronic control,
with data-diagnosis
1 full door and 2 half doors with
handle, lockable,

cooling machine on top, tropical
execution for ambient temperature +43°C,
forced air cooling, with automatic
defrosting and thaw water evaporation,

accessories : 7 grids GN 2/1
7 sets of supports

execution : stainless steel

KSAP BT 70/70



refrigerator/freezer - fish
Isselbaecher
KSAP BT 70/70-SUPREME 850

Dimensions : 1480 x 800 x 2080 mm
connection : 0,75 kW - 230/1/50

GN 2/1
temperature range :
right -6/+4°C (630 ltrs.)
left -15/-25°C (630 ltrs.)
- electronic control,
with data-diagnosis
2 doors with handle,
lockable,

cooling machine on top, tropical
execution for ambient temperature +43°C,
forced air cooling, with automatic
defrosting and thaw water evaporation,

accessories : 3 grids GN 2/1
12 plastic containers GN 1/1

execution : stainless steel

KSAP BT 105/35



refrigerator/freezer - fish
Isselbaecher
KSAP BT 105/35-SUPREME 85

Dimensions : 1480 x 800 x 2080 mm
connection : 0,75 kW - 230/1/50

content: 1265 ltrs. - GN 2/1
temperature range :
-6/+4°C (285)
-15/-25°C (980)
- electronic control,
with data-diagnosis
1 full door and 2 half doors with
handle, lockable,

cooling machine on top, tropical
execution for ambient temperature +43°C,
forced air cooling, with automatic
defrosting and thaw water evaporation,

accessories : 5 grids GN 2/1
6 plastic containers GN 2/1

execution : stainless steel