

SEF 1

salamander
Isselbaecher
SEF 1Dimensions : 540 x 400 x 390 mm
connection : 2 kW - 230/1/50with 3 supports
with 1 grid adjustable in height

execution : stainless steel

SEF 2

salamander
Isselbaecher
SEF 2Dimensions : 790 x 400 x 390 mm
connection : 4 KW - 400/3/50with 3 supports
with 1 grid adjustable in height

execution : stainless steel

SE 40/0

salamander
Isselbaecher
SE 40/0 *Dimensions : 400 x 450 x 500 mm
connection : 2 kW - 230/1/50cooking surface: 400 x 350
heating infinitively variable
adjustable, interlocked

execution : stainless steel

SE 40/0

salamander
Isselbaecher
SE 40/0 *Dimensions : 400 x 450 x 500 mm
connection : 2 kW - 230/1/50cooking surface: 400 x 350
heating infinitively variable
adjustable, interlocked

execution : stainless steel

SE 60/4

salamander
Isselbaecher
SE 60/4Dimensions : 600 x 450 x 500 mm
connection : 4 KW - 400/3/50cooking surface: 600 x 350
heating infinitively variable
adjustable, interlocked

execution : stainless steel

SE 80/0

salamander
Isselbaecher
SE 80/0Dimensions : 800 x 450 x 500 mm
connection : 6,0 kW - 400/3/50cooking surface: 800 x 350
heating infinitively variable
adjustable, interlocked

execution : stainless steel

SGM 60


 salamander
 Isselbaecher
 SGM 60

 Dimensions : 600 x 510 x 550 mm
 connection : gas 5,3 kW

 heating stepless adjustable in height
 1 grid removable

execution : stainless steel

SGF 80


 salamander
 Isselbaecher
 SGF 80

 Dimensions : 800 x 505 x 450 mm
 connection : gas 8,1 kW

 fixed heating
 1 grid removable

execution : stainless steel

SG/0


 salamander (gas)
 Isselbaecher
 SG/0

 Dimensions : 750 x 400 x 460 mm
 connection: 7,4 KW

 cooking zone: 575 x 400
 cooking zone in height continuously variable
 in height, interlocked,

execution : stainless steel

101.542


 salamander
 Isselbaecher
 101.542

 Dimensions : 400 x 455 x 515 mm
 connection : 3,0 KW - 230/1/50

- 2 heating elements
- wire shelf : 390 x 315 mm
- heating elements adjustable
in height, interlocked,
- heating up time 5 seconds
- half or full power
- timer with memory function
- less waste heat

execution : stainless steel

100.540


 salamander
 Isselbaecher
 100.540

 Dimensions : 570 x 500 x 520 mm
 connection : 4,5 kW - 400/3/50

- 3 heating elements
- heating elements adjustable
in height, interlocked,
- heating up time 5 seconds
- half or full power
- timer with memory function
- less waste heat

execution : stainless steel

100.546

salamander
Isselbaecher
100.546Dimensions : 570 x 500 x 520 mm
connection : 4,5 kW - 400/3/50

- 3 heating elements
- with warm keeping mode
- heating elements adjustable in height, interlocked,
- heating up time 5 seconds
- half or full power
- timer with memory function
- less waste heat

execution : stainless steel

101.544

salamander
Isselbaecher
101.544Dimensions : 735 x 530 x 515 mm
connection : 6,0 kW - 400/3/50

- 4 heating elements
- grid : 725 x 370 mm
- heating elements adjustable in height, interlocked,
- heating up time 5 seconds
- half or full power
- timer with memory function
- less waste heat

execution : stainless steel

Classic RH C

salamander
Isselbaecher
Classic RH CDimensions : 600 x 520 x 460 mm
connection : 3,6 kW - 400/3/50

- execution with heating elements
- main switch for full power, right - or left sided power and warm keeping mode
- mechanical timer 0-15 minutes with automatic switch - off
- plate identification

execution : stainless steel

Classic HL C

salamander
Isselbaecher
Classic HL CDimensions : 600 x 520 x 460 mm
connection : 4,6 kW - 400/3/50

- execution with Hi-Light
- main switch for full power, right - or left side power and warm keeping mode
- mechanical timer 0-15 minutes with automatic switch - off
- plate identification

execution : stainless steel