

slicer

Isselbaecher
kitchen equipment GmbH

Zentro Z 5 	slicer Isselbaecher Zentro Z 5 Dimensions : 390 x 305 x 300 mm connection : 0,17 KW - 230/1/50 gravity tilting slicer stainless steel full knife knife diam. : 170 mm accessories : 1 diamond-knife sharpener 1 rest holder 1 s/s tray execution : housing silver metallic
22 GS CE p 	slicer Isselbaecher 22 GS CE p Dimensions : 260 x 445 x 345 mm connection : 0,17 KW - 230/1/50 diagonal slicer knife diam. : 220 mm cutting thickness: 0-14 mm accessories : 1 knife sharpener execution : housing Aluminium
25 GS CE p 	slicer Isselbaecher 25 GS CE p Dimensions : 260 x 480 x 370 mm connection : 0,18 KW - 230/1/50 diagonal slicer knife diam. : 250 mm cutting thickness: 0-14 mm accessories : 1 knife sharpener execution : housing Aluminium
300/S-L CE p 	slicer Isselbaecher 300/S CE p Dimensions : 315 x 570 x 420 mm connection : 0,21 kW - 230/1/50 diagonal slicer knife diam. : 300 mm cutting thickness: 0-14 mm accessories : 1 knife sharpener execution : housing Aluminium
350/S CE p 	slicer Isselbaecher 350/S CE p Dimensions : 370 x 660 x 480 mm connection : 0,35 KW - 230/1/50 diagonal slicer knife diam : 350 mm cutting thickness: 0-14 mm accessories : 1 knife sharpener execution : housing Aluminium

slicer

AU 350/S CE + BLC 	slicer half-automatic Isselbaecher AU 350/S CE + BLC Dimensions : 680 x 515 x 550 mm connection : 0,38 kW - 230/1/50 diagonal slicer with automatic feed knife diam. : 350 mm cutting thickness: 0-14 mm accessories : 1 knife sharpener execution : housing Aluminium
250 	slicer Isselbaecher Quarzo 250 CE Dimensions : 550 x 570 x 485 mm connection : 0,25 kW - 230/1/50 diagonal slicer hollow grinded knife knife diam. : 250 mm cutting thickness : 0-14 mm slide surface : 150 x 190 mm accessories : 1 knife sharpener 1 rest holder execution : housing Aluminium anodized
300 	slicer Isselbaecher Quarzo 300 CE Dimensions : 550 x 605 x 520 mm connection : 0,3 KW - 230/1/50 diagonal slicer hollow grinded knife knife diam. : 300 mm cutting thickness : 0-14 mm slide surface : 175 x 235 mm accessories : 1 knife sharpener 1 rest holder execution : housing Aluminium anodized
330 	slicer Isselbaecher Gemma 330 CE Dimensions : 640 x 670 x 590 mm connection : 0,3 kW - 230/400/3/50 diagonal slicer hollow grinded knife knife diam. : 330 mm cutting thickness : 0-14 mm slide surface : 195 x 235 mm accessories : 1 knife sharpener 1 rest holder execution : housing Aluminium anodized
G 330 F 	heavy duty slicer Isselbaecher G 330 F Dimensions : 700 x 790 x 550 mm connection : 0,35 kW - 400/3/50 or 230/1/50 diagonal slicer knife made of stainless steel knife diam. : 330 mm cutting height : 225 mm cutting length : 320 mm cutting thickness : 0-15 mm

	accessories : 1 knife sharpener 1 rest holder execution : stainless steel
G 350 F 	heavy duty slicer Isselbaecher G 350 F Dimensions : 700 x 790 x 565 mm connection : 0,35 kW - 400/3/50 or 230/1/50 diagonal slicer knife made of stainless steel knife diam. : 350 mm cutting height : 235 mm cutting length : 320 mm cutting thickness : 0-15 mm accessories : 1 knife sharpener 1 rest holder execution : stainless steel
E 2000 	slicer Isselbaecher E 2000 Dimensions : 720 x 525 x 540 mm connection : 0,35 kW - 400/3/50 or 230/1/50 diagonal slicer hollow grinded knife knife diam. : 300 mm cutting height : 210 mm cutting length : 270 mm cutting thickness : 0-27 mm accessories : 1 knife sharpener 1 rest holder execution : stainless steel
ES 300 	slicer Isselbaecher ES 300 Dimensions : 635 x 580 x 420 mm connection : 0,30 kW 230/1/50 or 0,25 kW 400/3/50 Vertical slicer hollow grinded knife knife diam. : 300 mm cutting height : 210 mm cutting length : 250 mm cutting thickness : 0-15 mm accessories : 1 knife sharpener 1 rest holder execution : stainless steel
ATM-3 	slicer half-automatic Isselbaecher ATM-3 Dimensions : 728 x 565 x 600 mm connection : 0,6 kW - 400/3/50 230/1/50 diagonal sclicer, semi automatic with slide transport knife made of stainless steel knife diam. : 300 mm cutting height : 210 mm cutting length : 305 mm cutting thickness : 0-15 mm cutting speed : 36/min. switchable to manual use accessories : 1 knife sharpener

	1 rest holder execution : stainless steel
ATM-3 E 	slicer half-automatic Isselbaecher ATM-3 E Dimensions : 728 x 565 x 600 mm connection : 0,6 kW - 400/3/50 230/1/50 diagonal sclicer, semi automatic with slide transport knife made of stainless steel knife diam. : 300 mm cutting height : 210 mm cutting length : 305 mm cutting thickness : 0-15 mm electronic counter cutting speed : 22-50/min. switchable to manual use accessories : 1 knife sharpener 1 rest holder execution : stainless steel
VA 2000 	Slicer - fully automatic Isselbaecher VA 2000 Dimensions : 620 x 853 x 490 mm connection : 0,6 kW - 400/3/50 230/1/50 Vertical slicer, fully automatic with slide transport and lay down execution for spreading and stapeling knife made of stainless steel knife diam. : 300 mm cutting height : 195 mm cutting length : 255 mm cutting thickness : 0-10 mm slide surface : 275 x 330 mm max. height of pile : 80 mm spread distance : presetable cutting speed : 25-55/min. switchable to manual use accessories : 1 knife sharpener 1 rest holder execution : stainless steel
ATM-3 S 	slicer half-automatic Isselbaecher ATM-3 S Dimensions : 740 x 565 x 600 mm connection : 0,6 kW - 400/3/50 230/1/50 diagonal sclicer, semi automatic with slide transport knife made of stainless steel knife diam. : 330 mm cutting height : 225 mm cutting length : 305 mm cutting thickness : 0-15 mm cutting speed : 36/min. switchable to manual use accessories : 1 knife sharpener 1 rest holder execution : stainless steel

ATM-3 ES



slicer half-automatic
 Isselbaecher
 ATM-3 ES

Dimensions : 740 x 565 x 600 mm
 connection : 0,6 kW - 400/3/50
 230/1/50

diagonal sclicer, semi automatic
 with slide transport
 knife made of stainless steel
 knife diam. : 330 mm
 cutting height : 225 mm
 cutting length : 305 mm
 cutting thickness : 0-15 mm

electronic counter

cutting speed : 22-50/min.
 switchable to manual use

accessories : 1 knife sharpener
 1 rest holder

execution : stainless steel

General 2



Slicer - fully automatic
 Isselbaecher
 General 2

Dimensions : 565 x 670 x 600 mm
 connection : 0,6 kW - 400/3/50 or
 230/1/50

diagonal slicer 2-speed
 automatic slide
 automatic lay down execution

knife made of stainless steel
 knife diam. : 330 mm
 cutting height : 175 mm
 cutting length : 210 mm
 cutting thickness : 0-10 mm
 max. height of pile : 70 mm

execution : Aluminium

VA 4000



Slicer - fully automatic
 Isselbaecher
 VA 4000

Dimensions : 620 x 853 x 660 mm
 connection : 0,6 kW - 400/3/50
 230/1/50

Vertical slicer, fully automatic
 with slide transport and lay down execution
 for spreading and stapeling
 knife made of stainless steel
 knife diam. : 330 mm
 cutting height : 195 mm
 cutting length : 255 mm
 cutting thickness : 0-10 mm
 slide surface : 275 x 360 mm
 max. height of pile : 80 mm
 stack : 1 - 4
 spread distance : presetable

99 prgramms for laying down
 cutting speed : 25-55/min.
 switchable to manual use

accessories : 1 knife sharpener
 1 rest holder

execution : stainless steel

General 2 AT



Slicer - fully automatic
 Isselbaecher
 General 2 AT

Dimensions : 1500 x 840 x 1320 mm
 connection : 0,6 kW - 400/3/50
 230/1/50

diagonal slicer 2-speed
 automatic slide
 automatic lay down execution

1 base frame
 1 transport belt 1000 mm long

knife made of stainless steel
 knife diam. : 330 mm
 cutting height : 175 mm
 cutting length : 210 mm
 cutting thickness : 0-10 mm
 max. height of pile : 60 mm

no. of slices to be adjusted user defined
 distance between the portions
 adjustable continuously
 laying down in piles or spread
 spread distance stepless adjustable

execution : Aluminium

VA 4000 AT



Slicer - fully automatic
 Isselbaecher
 VA 4000 AT

Dimensions : 1270 x 853 x 1330 mm
 connection : 0,6 kW - 400/3/50
 230/1/50

Vertical slicer, fully automatic
 with slide transport and lay down execution
 for spreading and stapeling

1 base frame
 1 transport belt 880 - 280 mm

knife made of stainless steel
 knife diam. : 330 mm
 cutting height : 195 mm
 cutting length : 255 mm
 cutting thickness : 0-10 mm
 slide surface : 275 x 360 mm
 max. height of pile : 80 mm
 stack : 1 - 4
 spread distance : presetable

99 prgramms for laying down
 cutting speed : 25-55/min.
 switchable to manual use

accessories : 1 knife sharpener
 1 rest holder

execution : stainless steel