


rack ovens

	rack ovens
EPG 156 T 	gas "roll-in" baking oven Isselbaecher EPG 156 T Dimensions : 1010 x 860 x 1950 mm connection : gas 36 kW elt. 1,8 kW - 400/3/50 to take: 15 baking trays 600 x 400 mm - manual and automatic steam injection, - electronical programmable - alpha-numeric display - self diagnosis - 2 fan speeds - interior light - automatic dehumiditation with programmable opening before end of baking time - glass door, double glass accessories : 2 baking sheets aluminium 600 x 400 x 20 mm 1 support rack trolley execution : stainless steel
EKS 156 	support rack trolley EKS 156 Dimensions : 690 x 610 x 1845 mm - für 15 Bleche 600 x 400 mm - mit Kondensat-Auffangwanne execution : stainless steel
LV 156 	proofing cabinet LV 156 Dimensions : 990 x 650 x 1920 mm connection : 5 kW - 230/1/50 - for rack trolley EKS 156 - with 15 pair of rails for baking trays 600 x 400 mm execution : stainless steel
LD 25 	hand shower LD 25 - complete with hose made of stainless steel - stainless, connections and connections (2,5 m)
HKA 201 	condensation hood HKA 201 Dimensions : 1018 x 1086 x 300 mm with motor and aircooled condensator for expelled moisture condensation

rack ovens

EPG V15 T



gas "roll-in" baking oven
Isselbaecher
EPG V15 T

Dimensions : 1010 x 860 x 1950 mm
connection : gas 36 kW
elt. 5,8 kW - 400/3/50

to take:
15 baking trays 600 x 400 mm

- with built-in steam generator
- manual and automatic steam injection,
- electronical programmable
- alpha-numeric display
- self diagnosis
- 2 fan speeds
- interior light
- automatic dehumiditation with programmable opening before end of baking time
- glass door, double glass

accessories : 2 baking sheets aluminium
600 x 400 x 20 mm
1 support rack trolley

execution : stainless steel

EPE 156 T



electric "roll in" baking oven
Isselbaecher
EPE 156 T

Dimensions : 1010 x 860 x 1950 mm
connection : 31,8 kW - 400/3/50

to take:
15 baking trays 600 x 400 mm

- manual and automatic steam injection,
- electronical programmable
- alpha-numeric display
- self diagnosis
- 2 fan speeds
- interior light
- automatic dehumiditation with programmable opening before end of baking time
- glass door, double glass

accessories : 2 baking sheets aluminium
600 x 400 x 20 mm
1 support rack trolley

execution : stainless steel

EPE V15 T



electric "roll in" baking oven
Isselbaecher
EPE V15 T

Dimensions : 1010 x 860 x 1950 mm
connection : 35,8 kW - 400/3/50

to take:
15 baking trays 600 x 400 mm

- with built-in steam generator
- manual and automatic steam injection,
- electronical programmable
- alpha-numeric display
- self diagnosis
- 2 fan speeds
- interior light
- automatic dehumiditation with programmable opening before end of baking time
- glass door, double glass

accessories : 2 baking sheets aluminium
600 x 400 x 20 mm
1 support rack trolley

execution : stainless steel

rack ovens

B15M 	electric "roll in" baking oven Isselbaecher B15M Dimensions : 1000 x 825 x 2025 mm connection : 18,8 kW - 400/3/50 - inner dim. . 600 x 425 x 1400 mm - rails . for 15 baking sheets 600 x 400 mm - distance between tray rests : 90 mm - door with window made of heat resistant glass. accessories : 1 support rack trolley execution : stainless steel
B15M 	electric "roll in" baking oven Isselbaecher B15M Dimensions : 1000 x 825 x 2025 mm connection : 18,8 kW - 400/3/50 - inner dim. . 600 x 425 x 1400 mm - rails . for 15 baking sheets 600 x 400 mm - distance between tray rests : 90 mm - door with window made of heat resistant glass. accessories : 1 support rack trolley execution : stainless steel
GS15	proofing cabinet Isselbaecher GS15 * Dimensions : 1000 x 915 x 1980 mm connection : 5,1 kW - 400/3/50 for 15 trays 600 x 400 mm execution : stainless steel with glass door
K-15+H-KS-94 A 	electric "roll in" baking oven Isselbaecher K-15+H-KS-94 A Dimensions : 1000 x 1440 x 2120 mm connection : 24,0 kW - 400/3/50 - baking chamber to contain baking sheet trolley - steam generator - interior lightning - door with treble-glass - control panel with thermostate, temperature display on/off-switch, waterinjection and timer execution : stainless steel
K-15+H-KS-90 	electric "roll in" baking oven Isselbaecher K-15+H-KS-90 Dimensions : 1000 x 1440 x 2120 mm connection : 24,0 kW - 400/3/50 - baking chamber to contain baking sheet trolley - steam generator - interior lightning - door with treble-glass - following parameter programmable : baking temperature baking time beginning of water injection - up to 7 different program sequences programmable

rack ovens

	execution : stainless steel
SK-21-E+V-KS-94 	electric rotary baking oven Isselbaecher SK-21-E+V-KS-94 Dimensions : 1665 x 1405 x 2197 mm connection : 42,5 kW - 400/3/50 - baking chamber to contain baking sheet trolley - for baking sheets 600 x 400 mm - steam generator - interior lightning - control panel with thermostate, temperature display on/off-switch, waterinjection and timer execution : stainless steel
BSK-18/02 (60x40) 	trolley for baking oven BSK-18/02 (60x40) Dimensions : 456 x 614 x 1792 mm - 18 Paar Auflegewinkel zur Aufnahme von Backblechen 600 x 400 mm - Schienenabstand : 89 mm - mobile on 4 swivel casters 2 with brakes execution : stainless steel
SK-21-E+V-KS-90 	electric rotary baking oven Isselbaecher SK-21-E+V-KS-90 Dimensions : 1665 x 1405 x 2197 mm connection : 42,5 kW - 400/3/50 - baking chamber to contain baking sheet trolley - for baking sheets 600 x 400 mm - steam generator - interior lightning - following parameter programmable : baking temperature baking time beginning of water injection - up to 8 different program sequences programmable execution : stainless steel
SK-22-E+V-KS-94 	electric rotary baking oven Isselbaecher SK-22-E+V-KS-94 Dimensions : 1275 x 1705 x 2197 mm connection : 42,5 kW - 400/3/50 - baking chamber to contain baking sheet trolley - for baking sheets 600 x 400 mm - steam generator - interior lightning - control panel with thermostate, temperature display on/off-switch, waterinjection and timer execution : stainless steel

rack ovens

SK-22-E+V-KS-90 	electric rotary baking oven Isselbaecher SK-22-E+V-KS-90 Dimensions : 1275 x 1705 x 2197 mm connection : 42,5 kW - 400/3/50 - baking chamber to contain baking sheet trolley - for baking sheets 600 x 400 mm - steam generator - interior lightning - following parameter programmable : baking temperature baking time beginning of water injection - up to 8 different program sequences programmable execution : stainless steel
SR-21-E+V-KS-94 	electric rotary baking oven Isselbaecher SR-21-E+V-KS-94 Dimensions : 2023 x 1640 x 2197 mm connection : 57,0 kW - 400/3/50 - baking chamber to contain baking sheet trolley - for baking sheets 800 x 600 mm - steam generator - interior lightning - control panel with thermostate, temperature display on/off-switch, waterinjection and timer execution : stainless steel
SR-21-E+V-KS-90 	electric rotary baking oven Isselbaecher SR-21-E+V-KS-90 Dimensions : 2023 x 1640 x 2197 mm connection : 57,0 kW - 400/3/50 - baking chamber to contain baking sheet trolley - for baking sheets 800 x 600 mm - steam generator - interior lightning - following parameter programmable : baking temperature baking time beginning of water injection - up to 8 different program sequences programmable execution : stainless steel
SR-22-E+V-KS-94 	electric rotary baking oven Isselbaecher SR-22-E+V-KS-94 Dimensions : 1582 x 2031 x 2197 mm connection : 57,0 kW - 400/3/50 - baking chamber to contain baking sheet trolley - for baking sheets 800 x 600 mm - steam generator - interior lightning - control panel with thermostate, temperature display on/off-switch, waterinjection and timer execution : stainless steel

rack ovens

SR-22-E+V-KS-90 	electric rotary baking oven Isselbaecher SR-22-E+V-KS-90 Dimensions : 1582 x 2031 x 2197 mm connection : 57,0 kW - 400/3/50 - baking chamber to contain baking sheet trolley - for baking sheets 800 x 600 mm - steam generator - interior lightning - following parameter programmable : baking temperature baking time beginning of water injection - up to 8 different program sequences programmable execution : stainless steel
Shop-IN SI 1.0604 	electric rotary baking oven Isselbaecher Shop-IN SI 1.0604 Dimensions : 1000 x 1000 x 2330 mm connection : 34,6 kW - 400/3/50 - to hold baking trolley - built-in steam generator - to hold baking trolley with up to 18 pair of slides for baking trays 600 x 400 mm - digital control - door hinges on request right or left execution : stainless steel
Shop-IN SI 1.0604 	electric rotary baking oven Isselbaecher Shop-IN SI 1.0604 Dimensions : 1000 x 1000 x 2330 mm connection : 34,6 kW - 400/3/50 - to hold baking trolley - built-in steam generator - to hold baking trolley with up to 18 pair of slides for baking trays 600 x 400 mm - digital control - door hinges on request right or left execution : stainless steel
SW-SI 	trolley for baking oven SW-SI 1620 mm high with 18 pairs support angle to take baking trays 600 x 400 mm execution : stainless steel
Roll-IN RI 1.0608 	electric rotary baking oven Isselbaecher Roll-IN RI 1.0608 Dimensions : 1550 x 1450 x 2560 mm connection : 72,6 kW - 400/3/50 - to hold baking trolley - built-in steam generator - to hold baking trolley with up to 18 pair of slides for baking trays 600 x 800 mm - digital control - door hinges on request

right or left

execution : stainless steel