

table mounted refrigerated display

Isselbaecher
kitchen equipment GmbH

VARC6A 	table mounted refrigerated display Isselbaecher VARC6A Dimensions : 1437 x 396 x 245 mm connection : 0,20 kW - 230/1/50 1 refrigerated cold well for 6 x GN 1/3 1 cooling machine 1 glass top, tiltable - temperature: 0/+6°C execution: silver colour
VCLC6A 	table mounted refrigerated display Isselbaecher VCLC6A Dimensions : 1437 x 396 x 245 mm connection : 0,20 kW - 230/1/50 1 refrigerated cold well for 6 x GN 1/3 1 cooling machine 1 glass top, tiltable - temperature: 0/+6°C execution: gold colour
VEBC6A 	table mounted refrigerated display Isselbaecher VEBC6A Dimensions : 1437 x 396 x 245 mm connection : 0,20 kW - 230/1/50 1 refrigerated cold well for 6 x GN 1/3 1 cooling machine 1 glass top, tiltable - temperature: 0/+6°C execution: ebony colour
VARC8A 	table mounted refrigerated display Isselbaecher VARC8A Dimensions : 1789 x 396 x 245 mm connection : 0,20 kW - 230/1/50 1 refrigerated cold well for 8 x GN 1/3 1 cooling machine 1 glass top, tiltable - temperature: 0/+6°C execution: silver colour
VCLC8A 	table mounted refrigerated display Isselbaecher VCLC8A Dimensions : 1789 x 396 x 245 mm connection : 0,20 kW - 230/1/50 1 refrigerated cold well for 8 x GN 1/3 1 cooling machine 1 glass top, tiltable - temperature: 0/+6°C execution: gold colour

table mounted refrigerated display

Isselbaecher
kitchen equipment GmbH

VEBC8A 	table mounted refrigerated display Isselbaecher VEBC8A Dimensions : 1789 x 396 x 245 mm connection : 0,20 kW - 230/1/50 1 refrigerated cold well for 8 x GN 1/3 1 cooling machine 1 glass top, tiltable - temperature: 0/+6°C execution: ebony colour
VP 3014N 	table mounted refrigerated display Isselbaecher VP 3014N Dimensions : 1420 x 320 x 240 mm connection . 0,15 kW - 230/1/50 1 refrigerated cold well for 6 x GN 1/4 1 cooling machine at right side - temperature: +2/+10°C execution : stainless steel
VP 3016N 	table mounted refrigerated display Isselbaecher VP 3016N Dimensions : 1600 x 320 x 240 mm connection . 0,15 kW - 230/1/50 1 refrigerated cold well for 7 x GN 1/4 1 cooling machine at right side - temperature: +2/+10°C execution : stainless steel
VP 3018N 	table mounted refrigerated display Isselbaecher VP 3018N Dimensions : 1800 x 320 x 240 mm connection . 0,15 kW - 230/1/50 1 refrigerated cold well for 8 x GN 1/4 1 cooling machine at right side - temperature: +2/+10°C execution : stainless steel
VP 3020N 	table mounted refrigerated display Isselbaecher VP 3020N Dimensions : 1960 x 320 x 240 mm connection . 0,15 kW - 230/1/50 1 refrigerated cold well for 9 x GN 1/4 1 cooling machine at right side - temperature: +2/+10°C execution : stainless steel
VP 3021N 	table mounted refrigerated display Isselbaecher VP 3021N Dimensions : 2150 x 320 x 240 mm connection . 0,15 kW - 230/1/50 1 refrigerated cold well for 10 x GN 1/4 1 cooling machine at right side - temperature: +2/+10°C execution : stainless steel

table mounted refrigerated display

Isselbaecher
kitchen equipment GmbH

VP 3025N 	table mounted refrigerated display Isselbaecher VP 3025N Dimensions : 2500 x 320 x 240 mm connection . 0,15 kW - 230/1/50 1 refrigerated cold well for 12 x GN 1/4 1 cooling machine at right side - temperature: +2/+10°C execution : stainless steel
VP 3014Q 	table mounted refrigerated display Isselbaecher VP 3014Q Dimensions : 1420 x 320 x 440 mm connection . 0,15 kW - 230/1/50 1 refrigerated cold well for 6 x GN 1/4 1 cooling machine at right side 1 angled glass top - temperature: +2/+10°C execution : stainless steel
VP 3016Q 	table mounted refrigerated display Isselbaecher VP 3016Q Dimensions : 1600 x 320 x 440 mm connection . 0,15 kW - 230/1/50 1 refrigerated cold well for 7 x GN 1/4 1 cooling machine at right side 1 angled glass top - temperature: +2/+10°C execution : stainless steel
VP 3018Q 	table mounted refrigerated display Isselbaecher VP 3018Q Dimensions : 1800 x 320 x 440 mm connection . 0,15 kW - 230/1/50 1 refrigerated cold well for 8 x GN 1/4 1 cooling machine at right side 1 angled glass top - temperature: +2/+10°C execution : stainless steel
VP 3020Q 	table mounted refrigerated display Isselbaecher VP 3020Q Dimensions : 1960 x 320 x 440 mm connection . 0,15 kW - 230/1/50 1 refrigerated cold well for 9 x GN 1/4 1 cooling machine at right side 1 angled glass top - temperature: +2/+10°C execution : stainless steel

table mounted refrigerated display

Isselbaecher
kitchen equipment GmbH

VP 3025Q 	table mounted refrigerated display Isselbaecher VP 3025Q Dimensions : 2500 x 320 x 440 mm connection . 0,15 kW - 230/1/50 1 refrigerated cold well for 12 x GN 1/4 1 cooling machine at right side 1 angled glass top - temperature: +2/+10°C execution : stainless steel
VP 3021Q 	table mounted refrigerated display Isselbaecher VP 3021Q Dimensions : 2150 x 320 x 440 mm connection . 0,15 kW - 230/1/50 1 refrigerated cold well for 10 x GN 1/4 1 cooling machine at right side 1 angled glass top - temperature: +2/+10°C execution : stainless steel
VV 100 	table mounted refrigerated display Isselbaecher VV 100 Dimensions : 1000 x 450 x 530 mm connection . 0,15 kW - 230/1/50 temp.-range: +2°C/+5°C consisting of: 1 display case with 2 wire shelves adjustable in height 2 glass sliding doors at operator's side - glass screen at customer side 1 cooling machine at right side plugg-in unit with forced-air cooling execution : stainless steel
EVF630 	table mounted refrigerated display Isselbaecher EVF630 Dimensions : 755 x 770 x 590 mm connection : 0,39 kW - 230/1/50 temp.-range: +4°C - 10°C - with clipboard - to take 2 x GN 1/1 execution : stainless steel
EVF970 	table mounted refrigerated display Isselbaecher EVF970 Dimensions : 1092 x 780 x 590 mm connection : 0,95 kW - 230/1/50 temp.-range: +4°C - 10°C - with clipboard - for storing 3 x GN 1/1 execution : stainless steel

table mounted refrigerated display

Isselbaecher
kitchen equipment GmbH

APV - 2 	table mounted refrigerated display Isselbaecher APV-2 Dimensions : 800 x 800 x 650 mm connection : 0,32 kW - 230/1/50 temp.-range: +5°C/+12°C consisting of: 1 display case glass all 4 sides 1 indertediate glass board 1 front screen tiltable for cleaning 1 interior light underneath cover 2 glass sliding doors at operator's side - automatic defrosting and thaw water evaporation - digital temperature display - plugg-in unit with forced-air cooling execution : stainless steel
APV - 3 	table mounted refrigerated display Isselbaecher APV-3 Dimensions : 1125 x 800 x 650 mm connection : 0,37 kW - 230/1/50 temp.-range: +5°C/+12°C consisting of: 1 display case glass all 4 sides 1 indertediate glass board 1 front screen tiltable for cleaning 1 interior light underneath cover 2 glass sliding doors at operator's side - automatic defrosting and thaw water evaporation - digital temperature display - plugg-in unit with forced-air cooling execution : stainless steel
APV - 4 	table mounted refrigerated display Isselbaecher APV-4 Dimensions : 1450 x 800 x 650 mm connection : 0,56 kW - 230/1/50 temp.-range: +5°C/+12°C consisting of: 1 display case glass all 4 sides 1 indertediate glass board 1 front screen tiltable for cleaning 1 interior light underneath cover 2 glass sliding doors at operator's side - automatic defrosting and thaw water evaporation - digital temperature display - plugg-in unit with forced-air cooling execution : stainless steel
AVM 130 - S 	table mounted refrigerated display Isselbaecher AVM 130-S Dimensions : 1300 x 525 x 700 mm connection : 0,4 kW - 230/1/50 Temp.-range: +6°/+15°C - unit with forced-air cooling and with built-in cooling machine incl. interior lighting, - automatic defrosting and thaw water evaporation, - sliding doors at user side, - at customer side panorama screen accessories : 2 s/s wire shelves execution : stainless steel

table mounted refrigerated display

Isselbaecher
kitchen equipment GmbH

AVM 145-S 	table mounted refrigerated display Isselbaecher AVM 145-S Dimensions : 1450 x 525 x 700 mm connection : 0,4 kW - 230/1/50 Temp.-range: +6°/+15°C - unit with forced-air cooling and with built-in cooling machine - incl. interior lighting, - automatic defrosting and thaw water evaporation, - sliding doors at user side, - at customer side panorama screen accessories : 2 s/s wire shelves execution : stainless steel
AVM 130-K 	table mounted refrigerated display Isselbaecher AVM 130-K Dimensions : 1300 x 525 x 700 mm connection : 0,4 kW - 230/1/50 Temp.-range: +6°/+15°C - unit with forced-air cooling and with built-in cooling machine - incl. interior lighting, - automatic defrosting and thaw water evaporation, - sliding doors at user side, - at customer side 6 pcs. plexiglass flaps accessories : 2 s/s wire shelves execution : stainless steel
AVM 145-K 	table mounted refrigerated display Isselbaecher AVM 145-K Dimensions : 1450 x 525 x 700 mm connection : 0,4 kW - 230/1/50 Temp.-range: +6°/+15°C - unit with forced-air cooling and with built-in cooling machine - incl. interior lighting, - automatic defrosting and thaw water evaporation, - sliding doors at user side, - at customer side 6 pcs. plexiglass flaps accessories : 2 s/s wire shelves execution : stainless steel
AKV-S 96 	table mounted refrigerated display Isselbaecher AKV-S 96 Dimensions : 910 x 508 x 550 mm connection : 0,19 kW - 230/1/50 temp.-range: +4/+12°C consisting of: 1 display case with 1 board 1 interior light 2 glass sliding doors at operator's side - glass sliding doors at customer side 1 cooling machine at right side with plug, circulated air refrigeration, Thermostat, automatic defrosting and thaw water evaporation execution : stainless steel

AKV-S 116 	table mounted refrigerated display Isselbaecher AKV-S 116 Dimensions : 1110 x 508 x 550 mm connection : 0,19 kW - 230/1/50 temp.-range: +4/+12°C consisting of: 1 display case with 1 board 1 interior light 2 glass sliding doors at operator's side - glass sliding doors at customer side 1 cooling machine at right side with plug, circulated air refrigeration, Thermostat, automatic defrosting and thaw water evaporation execution : stainless steel
AKV-S 146 	table mounted refrigerated display Isselbaecher AKV-S 146 Dimensions : 1410 x 508 x 550 mm connection : 0,19 kW - 230/1/50 temp.-range: +4/+12°C consisting of: 1 display case with 1 board 1 interior light 2 glass sliding doors at operator's side - glass sliding doors at customer side 1 cooling machine at right side with plug, circulated air refrigeration, Thermostat, automatic defrosting and thaw water evaporation execution : stainless steel
AKV-S 147 	table mounted refrigerated display Isselbaecher AKV-S 147 Dimensions : 1410 x 508 x 700 mm connection : 0,24 kW - 230/1/50 temp.-range: +4/+12°C consisting of: 1 display case with 2 shelves 1 interior light 2 glass sliding doors at operator's side - glass sliding doors at customer side 1 cooling machine at right side with plug, circulated air refrigeration, Thermostat, automatic defrosting and thaw water evaporation execution : stainless steel
AKV-S 96KL 	table mounted refrigerated display Isselbaecher AKV-S 96KL Dimensions : 910 x 508 x 550 mm connection : 0,19 kW - 230/1/50 temperature range : +6°C/+12°C consisting of: 1 display case with 1 board 1 interior light 2 glass sliding doors at operator's side 2 distributionflaps at customer's side 1 cooling machine at right side with plug, circulated air refrigeration, Thermostat, automatic defrosting and thaw water evaporation execution : stainless steel

AKV-S 116KL



table mounted refrigerated display
Isselbaecher
AKV-S 116KL

Dimensions : 1110 x 508 x 550 mm
connection : 0,19 kW - 230/1/50

temperature range : +6°C/+12°C
consisting of:
1 display case with 1 board
1 interior light
2 glass sliding doors at operator's side
4 take out flaps at customers side

1 cooling machine at right side
with plug, circulated air refrigeration,
Thermostat, automatic defrosting and
thaw water evaporation

execution : stainless steel

AKV-S 146KL



table mounted refrigerated display
Isselbaecher
AKV-S 146KL

Dimensions : 1410 x 508 x 550 mm
connection : 0,19 kW - 230/1/50

temperature range : +6°C/+12°C
consisting of:
1 display case with 1 board
1 interior light
2 glass sliding doors at operator's side
4 take out flaps at customers side

1 cooling machine at right side
with plug, circulated air refrigeration,
Thermostat, automatic defrosting and
thaw water evaporation

execution : stainless steel

AKV-S 147KL



table mounted refrigerated display
Isselbaecher
AKV-S 147KL

Dimensions : 1410 x 508 x 700 mm
connection : 0,24 kW - 230/1/50

temperature range : +6°C/+12°C
consisting of:
1 display case with 2 shelves
1 interior light
2 glass sliding doors at operator's side
6 distribution flaps at customer side

1 cooling machine at right side
with plug, circulated air refrigeration,
Thermostat, automatic defrosting and
thaw water evaporation

execution : stainless steel