







	taps
<p>1S.4001.67.33</p> 	<p>mixing tap, wall mounted 1/2" Isselbaecher 1S.4001.67.33</p> <p>2-hole wall mounted mixing tap for cold and warm water 1/2" drain 300 mm height 155 mm</p>
<p>1E.4053.19.11</p> 	<p>mixing tap 3/4" (wall mounted) Isselbaecher 1E.4053.19.11</p> <p>with swivelling drain for cold and warm water 3/4" drain 300 mm height 150 mm</p>
<p>2E.4015.19.11</p> 	<p>hand shower 1/2" (wall mounted) Isselbaecher 2E.4015.19.11</p> <p>1/2" for cold and hot water, with swivel spout</p>
<p>1S.2402.05.33</p> 	<p>1-hole mixing tap 1/2" Isselbaecher 1S.2402.05.33</p> <p>for cold- and hot water 1/2" drain 250 mm height 150 mm</p>
<p>1E.3014.07.11</p> 	<p>mixing tap 1/2" Isselbaecher 1E.3014.07.11</p> <p>2-hole mixing tap for cold and warm water 1/2" drain 300 mm height : 150 mm</p>
<p>1E.3017.20.11</p> 	<p>mixing tap 3/4" Isselbaecher 1E.3017.20.11</p> <p>2-hole mixing tap for cold and warm water 3/4" with 80 mm thread 3/4" and thread diam. inside : 18 mm drain 300 mm height 250 mm</p>

# taps

**Isselbaecher**  
kitchen equipment GmbH

<p>1S.2962.00.81</p> 	<p>1-lever mixing tap 1/2" Isselbaecher 1S.2962.00.81</p> <p>for cold- and hot water 1/2" drain 260 mm hight 135 mm</p>
<p>2S.2011.00.23</p> 	<p>hand shower 1/2" (1-hole) Isselbaecher 2S.2011.00.23</p> <p>with 80 mm thread 1-hole 1/2", connection to cold water or warm water</p>
<p>3E.3014.35.11</p> 	<p>shower 1/2" Isselbaecher 3E.3014.35.11</p> <p>hand shower w. 2 hole stand mixing tap 1/2" for h/c water with swivel outlet conn. thread 80 mm</p>
<p>1E.2263.85.11</p> 	<p>1-hole column-mixing tap Isselbaecher 1E.2263.85.11</p> <p>with swivelling drain for cold- hot water with drainage-emptying drain 350 mm height : 570 mm</p>
<p>K.12.JK.52.000N23</p> 	<p>1-hole sensor mixing tap Isselbaecher K.12.JK.52.000N23 *</p> <p>connection : 230/6V</p> <p>one-hole sensor mixing tap with low drain</p> <p>execution : chrome</p>
<p>150.010.11</p> 	<p>1-hole sensor mixing tap Isselbaecher 150.010.11</p> <p>Dimensions : x 147 x 255 mm connection : 230/1/50</p> <ul style="list-style-type: none"> <li>- dual infrared sensors ( automatic setting feature)</li> <li>- warm- and coldwater connection with flexible pressure hose</li> <li>- built-in check-valves and dirt collecting sieve</li> <li>- temporary-off (cleaning) and continuous-on (filling) with Iqua-Klick activatable</li> <li>- follow-up timer, sensor</li> </ul>

sensitivity adjustable with iqua-click  
adjustable  
- 24 hours hygienic flush with  
activatable with iqua-click  
- alternatively in battery-run execution