













tin opener

Isselbaecher
kitchen equipment GmbH

<p>DO 5</p> 	<p>tin opener Isselbaecher DO 5</p> <p>manual appliance for round and square tins up to 30 kg tongs type tin opener suitable for all of tin heights</p> <p>execution : stainless steel</p>
<p>DO 2</p> 	<p>tin opener Isselbaecher DO 2</p> <p>for tins up to 33 cm height execution: hammer effect enamel</p>
<p>DO 1</p> 	<p>tin opener Isselbaecher DO 1</p> <p>for tins up to 40 cm height execution: hammer effect enamel</p>
<p>DO 11</p> 	<p>tin opener Isselbaecher DO 11</p> <p>for tins up to 40 cm height with rotating plate execution: hammer effect enamel</p>
<p>DO 10</p> 	<p>tin opener Isselbaecher DO 10</p> <p>for tins up to 40 cm height execution : stainless steel</p>
<p>DO 101</p> 	<p>tin opener Isselbaecher DO 101</p> <p>for tins up to 40 cm height with rotating plate execution : stainless steel</p>

tin opener

Isselbaecher
kitchen equipment GmbH

<p>DO 51 C</p> 	<p>tin opener Isselbaecher DO 51 C</p> <p>for round and oval tins up to 35 cm height and 10 kg weight with driven rotating knife and with stainless steel base plate</p>
<p>DO 50 C</p> 	<p>tin opener Isselbaecher DO 50 C</p> <p>for round and oval tins up to 35 cm height and 10 kg weight</p> <p>with driven rotating knife, with stainless steel base plate</p>
<p>DO 55</p> 	<p>tin opener Isselbaecher DO 55</p> <p>connection : 0,16 kW - 230/1/50</p> <p>for round and square tins up to 32 cm height and 10 kg weight</p> <p>with driven rotating knife and stepless adjustable by means of gas spring integrated in shaft</p> <p>execution : stainless steel</p>
<p>DO 65/1</p> 	<p>tin opener Isselbaecher DO 65/1</p> <p>connection : 0,18 kW - 400/3/50</p> <p>with 1 x 75 rpm. for round and oval tins up to 30 cm height and 10 kg weight</p> <p>with driven rotating knife and additional peak knife with bracket for small square tins</p>
<p>DO 65/2</p> 	<p>tin opener Isselbaecher DO 65/2</p> <p>connection : 0,2 kW - 400/3/50</p> <p>with 2 speeds, 50/100 rpm. for round and square tins up to 30 cm height and 10 kg weight</p> <p>with driven rotating knife and additional peak knife w. holder for small square tins</p>
<p>DO 66/1</p> 	<p>tin opener Isselbaecher DO 66/1</p> <p>connection : 0,18 kW - 400/3/50</p> <p>with 1 x 75 rpm. for round and square tins up to 40 cm height and 10 kg weight</p> <p>with driven rotating knife and additional peak knife w. holder for small square tins</p>

DO 66/2



tin opener
Isselbaecher
DO 66/2

connection : 0,2 kW - 400/3/50

with 2 speeds, 50/100 rpm.
for round and square tins up to
40 cm height and 10 kg weight

with driven rotating knife and
additional peak knife w. holder
for small square tins