

IP400



waste compactor
Isselbaecher
IP400

Dimensions : 580 x 600 x 1645 mm
connection : 0,75 kW - 230/1/50

- up to 80 % less volume
- compact. force: 3000 kg
- compact. ratio: approx 5:1
- package dim. : approx. 375x375x380 mm
- bag weight : 16-18 kg
- cycle time : 14 sec.
- c/w safety switch
at trolley and chute
- operation display and
indication if container is full

accessories:

- trolley
- 100 plastic bags
- tying wiring
- tying tool

execution : stainless steel

IP500



waste compactor
Isselbaecher
IP500

Dimensions : 680 x 680 x 1755 mm
connection : 0,75 kW - 230/1/50

- up to 80 % less volume
- compact. force: 4500 kg
- compact. ratio: approx 5:1
- package dim. : approx. 500x500x430 mm
- bag weight : 25-30 kg
- cycle time : 23 sec.
- c/w safety switch
at trolley and chute
- operation display and
indication if container is full

accessories:

- trolley
- 100 plastic bags
- tying wiring
- tying tool

execution : stainless steel

IP600



waste compactor
Isselbaecher
IP600

Dimensions : 840 x 870 x 1930 mm
connection : 0,75 kW - 230/1/50

- up to 80 % less volume
- compact. force: 5000 kg
- compact. ratio: approx 5:1
- package dim. : approx. 600x600x580 mm
- bag weight : 40-45 kg
- cycle time : 23 sec.
- c/w safety switch
at trolley and chute
- operation display and
indication if container is full

accessories:

- trolley
- 100 plastic bags
- tying wiring
- tying tool

execution : stainless steel

IP700



waste compactor
Isselbaecher
IP700

Dimensions : 840 x 870 x 1930 mm
connection : 0,75 kW - 230/1/50

- up to 80 % less volume
- compact. force: 1000 kg
- compact. ratio: approx 5:1
- package dim. : 240l waste bin
- bag weight : 40-45 kg
- cycle time : 17 sec.
- c/w safety switch
at door and waste bin
- operation display and
indication if container is full

execution : stainless steel