

523/1



waste disposer
Isselbaecher
523/1

Dimensions : 789 x 405 x mm
connection : 0,55 KW - 230/1/50

for up to 200 covers
capacity: 100-150 kg/h
mounted below sink
water consumption: 11-14 ltrs./min.
1 switch box

523/3



waste disposer
Isselbaecher
523/3

Dimensions : 789 x 405 x mm
connection : 0,55 kW - 40073/50

for up to 200 covers
capacity: 100-150 kg/h
mounted below sink
water consumption: 11-14 ltrs./min.
1 switch box

525/1



waste disposer
Isselbaecher
525/1

Dimensions : 330 x 355 x 630 mm
connection : 0,55 KW - 230/1/50

for up to 400 covers
Leistung: 200 kg/h,
to be welded into work table
water consumption: 11 - 14 ltrs./min.
1 switch box

dim. of cut-out of table: 324 x 298 mm

525/3



waste disposer
Isselbaecher
525/3

Dimensions : 330 x 355 x 630 mm
connection : 0,55 kW - 40073/50

for up to 400 covers
Leistung: 200 kg/h,
to be welded into work table
water consumption: 11 - 14 ltrs./min.
1 switch box

dim. of cut-out of table: 324 x 298 mm

526/1



waste disposer
Isselbaecher
526/1

Dimensions : 400 x 600 x 865 mm
connection : 0,55 KW - 230/1/50

for up to 200 covers
capacity : 200 kg/hr.
free standing model
water consumption: 11-14 ltrs./min.
1 switch box

526/3



waste disposer
Isselbaecher
526/3

Dimensions : 400 x 600 x 865 mm
connection : 0,55 kW - 40073/50

for up to 200 covers
capacity : 200 kg/hr.
free standing model
water consumption: 11-14 ltrs./min.
1 switch box

723/3



waste disposer
Isselbaecher
723/3

Dimensions : 565 x x 550 mm
connection : 1,1 KW - 400/3/50

suitable for tougher types of waste
for up to 400 covers
capacity : 200 kg/hr.
mounted below sink
water consumption: 11-14 ltrs./min.
1 switch box

725/3



waste disposer
Isselbaecher
725/3

Dimensions : 338 x 474 x 725 mm
connection : 1,1 KW - 400/3/50

suitable for tougher types of waste
for up to 850 covers
capacity : 400 kg/hr.
to be welded into work table
water consumption: 11 - 14 ltrs./min.
1 switch box

726/3



waste disposer
Isselbaecher
726/3

Dimensions : 400 x 600 x 850 mm
connection : 0,55 kW - 40073/50

suitable for tougher types of waste
for up to 850 covers
capacity : 400 kg/hr.
free standing model
water consumption: 11-14 ltrs./min.
1 switch box

825/3



waste disposer
Isselbaecher
825/3

Dimensions : 360 x 530 x 795 mm
connection : 2,2 kW - 400/3/50

suitable for very tough types of waste
free standing model
capacity : 600 kg/hr.
to be welded into work table
water consumption: 11 - 14 ltrs./min.
1 switch box

826/3



waste disposer
Isselbaecher
826/3

Dimensions : 430 x 600 x 850 mm
connection : 0,55 kW - 40073/50

suitable for very tough types of waste
free standing model
cpapcity : 600 kg/hr.
free standing model
water consumption: 11-14 ltrs./min.
1 switch box